

PRODUCT DATA SHEET

SikaWall®-500 Wet Dash

Wet Dash Render

PRODUCT DESCRIPTION

SikaWall®-500 Wet Dash is a factory batched, cement based dry mixed render. This product is through coloured and should be combined with decorative aggregates. The SikaWall®-500 Wet Dash combined with decorative aggregates only require the addition of clean potable water; no other material should be added.

USES

Render to achieve a wet dash finish when combined with decorative aggregates.

CHARACTERISTICS / ADVANTAGES

- Excellent finish in all weather conditions
- Available in a range of natural colours

PRODUCT INFORMATION

Packaging	25 kg bag
Shelf Life	12 Months from date of manufacture
Storage Conditions	Dry frost free conditions
Reaction to Fire	A1

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Product intended for professional use.
- It is advisable when completing the different finishes, to take into account the hardening time, which will vary according to climatic conditions.
- Avoid applications on substrates exposed to direct sun or in hot drying winds. Do not apply on over heated substrates. In hot conditions dampen the substrate prior to application. Dampen the render after application.
- Do not apply to a frozen substrate or on thawing substrates. Do not use in freezing conditions.
- Take precautions during damp climatic conditions. (Discolouration could occur).
- Do not apply on very wet substrates or where there are wet patches. (Discolouration could occur).
- Minimum application temperatures: +5 °C for light colours, +8 °C for dark colours.
- Over 30 °C, special precautions must be taken. In order to reduce the risk of colour differences after drying, always use the same batch number only for the same facade

ECOLOGY, HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye / face protection. This product contains materials which may cause an allergic reaction, is irritating to eyes and harmful if swallowed. In case of contact, seek medical advice. Keep out of the reach of children. Read and follow the guidelines in the Health and Safety data sheet for this product.

SUBSTRATE QUALITY / PRE-TREATMENT

Suitable Substrates

This product has been designed to be applied to SikaWall®-530 Top Coat for Masonry substrates.

MIXING

- Mix one 25 bag of SikaWall-500 Wet Dash with one 25 bag of decorative aggregate.
- Mixed with 7-8 L of water.
- Mix with a concrete mixer or paddle mixer.
- Mix for approximately 5 minutes.
- No other materials should be added.
- Care should be taken not to over mix or over trowel as this will reduce the adhesion performance.

APPLICATION

SikaWall-500 Wet Dash is a render finish which can be applied by hand or by Tyrolean Type gun onto SikaWall-530 Top Coat.

The finish must be applied onto SikaWall-530 Top Coat before skin formation has taken place.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

SikaWall®-500 Wet Dash
April 2022, Version 01.01
021810101000000100

SikaWall-500WetDash-en-GB-(04-2022)-1-1.pdf