According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sika® Aktivator-100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

: +44 (0)1707 394444 Telephone : +44 (0)1707 329129 Telefax E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

H315: Causes skin irritation. Skin irritation, Category 2

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms











Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing pro-

tection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391 Collect spillage.

#### Hazardous components which must be listed on the label:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics N-(3-(trimethoxysilyl)propyl)ethylenediamine tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)	
	Registration number			
Hydrocarbons, C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>=80	
isoalkanes, cyclics	927-510-4	Skin Irrit. 2; H315		
Contains:	01-2119475515-33-	STOT SE 3; H336		
cyclohexane >= 2 %	XXXX [corresponding	Asp. Tox. 1; H304		
	group CAS 64742-49- 0]	Aquatic Chronic 2; H411		
ethanol	64-17-5	Flam. Liq. 2; H225	>= 5 - < 10	
	200-578-6 01-2119457610-43-	Eye Irrit. 2; H319		
	XXXX	specific concentration limit		
		Eye Dam. 2; H319		
		>= 50 %		
N-(3-	1760-24-3	Eye Dam. 1; H318	>= 2.5 - < 3	
(trimethoxysi-	217-164-6	Skin Sens. 1B; H317	,	
lyl)propyl)ethylenediamine	01-2119970215-39-	STOT SE 3; H335		
Contains:	XXXX	(Respiratory system)		
N,N'-bis[3-				
(trimethoxysi-				
lyl)propyl]ethylenediamine <= 3 %				
1-(2-Aminoethyl)-2,2-dimethoxy-1-				
aza-2-silacyclopentane <= 3 %				
tris(dodecylbenzenesulphonato-	61417-55-8	Acute Tox. 4; H302	>= 2,5 - < 3	
O)(propan-2-olato)titanium	262-777-4	Skin Corr. 1B; H314		
		Eye Dam. 1; H318		
		Skin Sens. 1; H317		

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Allergic reactions
Excessive lachrymation

Excessive laciliyinallor

Erythema Dermatitis Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).

irritant effects sensitising effects

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

### 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

**Environmental precautions** Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store

in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *	
		of exposure)	ters *		
ethanol	64-17-5	TWA	1.000 ppm	GB EH40	
			1.920 mg/m3		
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be				
	used.				

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
	Further information: Indicative, Identifies the possibility of significant uptake through the skin				
		TWA	200 ppm 266 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The as signed substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	250 ppm 333 mg/m3	GB EH40	

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

# 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0.1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, Skin and body protection

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### **Environmental exposure controls**

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state liauid Colour colourless

hydrocarbon-like Odour

Melting point/range / Freezing : No data available

point

Boiling point/boiling range : ca. 78 °C

Flammability (solid, gas) : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : 7 %(V)

per flammability limit

Lower explosion limit /

Lower flammability limit

: 0,6 %(V)

Flash point

: ca. -4 °C

Method: closed cup

Auto-ignition temperature

200 °C

Decomposition temperature

: No data available

Hq

Not applicable

substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, kinematic

< 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 75,9935 hPa

Density : ca. 0,727 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

Hazardous decomposition : methanol

products

mounano

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Not classified due to lack of data.

#### Components:

#### N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 2.995 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

## Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data.

# Reproductive toxicity

Not classified due to lack of data.

## STOT - single exposure

May cause drowsiness or dizziness.

## STOT - repeated exposure

Not classified due to lack of data.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

#### **Product:**

: The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

This substance/mixture contains no components considered Assessment

to be either persistent, bioaccumulative and toxic (PBT), or

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

## 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

ADR : UN 1866 IMDG : UN 1866 IATA : UN 1866

14.2 UN proper shipping name

ADR : RESIN SOLUTION

IMDG : RESIN SOLUTION

(n hontone)

(n-heptane)

IATA : Resin solution

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 3 IMDG : 3 IATA : 3

14.4 Packing group

**ADR** 

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

**IMDG** 

Packing group : II
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 353

ger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

**IMDG** 

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

: Not applicable

Control of Major Accident Hazards Regulations P5c FLAMMABLE LIQUIDS 2015 (COMAH)

2010 (00111111)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

34

#### E2 ENVIRONMENTAL HAZARDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 94% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 94% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways. H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure 2006/15/EC : Europe. Indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2006/15/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sika® Aktivator-100

Date of last issue: 12.07.2023 Version 15.0 Print Date 29.02.2024

Revision Date: 29.11.2023

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Classification procedure:

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture:

# Flam. Liq. 2 H225 Based on product data or assessment Skin Irrit. 2 H315 Calculation method Eye Dam. 1 H318 Calculation method

Skin Sens. 1 H317 Calculation method STOT SE 3 H336 Calculation method Asp. Tox. 1 H304 Calculation method Aquatic Chronic 2 H411 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN