

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaBond® PVA Wood Adhesive Ultra

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

##### Additional Labelling

EUH208 Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Please use treated articles responsibly.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

---

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number         | Classification                                              | Concentration<br>(% w/w) |
|---------------|---------------------------------------------------------------|-------------------------------------------------------------|--------------------------|
| propan-2-ol   | 67-63-0<br>200-661-7<br>603-117-00-0<br>01-2119457558-25-XXXX | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336 | >= 1 - < 2,5             |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025

Version 4.2

Print Date 16.03.2026

Revision Date: 16.03.2026

|                                                                                               |                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                      |
|-----------------------------------------------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | 55965-84-9<br>613-167-00-5<br>01-2120764691-48-XXXX | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 2; H310<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 100100<br>M-Factor (Chronic aquatic toxicity): 100100<br><br>specific concentration limit<br>Skin Corr. 1C; H314<br>>= 0,6 %<br><br>specific concentration limit<br>Skin Irrit. 2; H315<br>0,06 - < 0,6 %<br><br>specific concentration limit<br>Eye Irrit. 2; H319<br>0,06 - < 0,6 %<br><br>specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br><br>specific concentration limit<br>Eye Dam. 1; H318<br>>= 0,6 % | >= 0,0002 - < 0,0015 |
|-----------------------------------------------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

|                                       |                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                         |                      |
|---------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| 2-methyl-2H-isothiazol-3-one<br>(MIT) | 2682-20-4<br>220-239-6<br>613-326-00-9<br>01-2120764690-50-XXXX | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 3; H311<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 1010<br>M-Factor (Chronic aquatic toxicity): 11<br><br>specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 200 mg/kg | >= 0,0002 - < 0,0015 |
|---------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects and symptoms.

Risks : No known significant effects or hazards.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

### 6.2 Environmental precautions

Environmental precautions : No special environmental precautions required.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
No special handling advice required.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components  | CAS-No. | Value type (Form of exposure) | Control parameters *               | Basis * |
|-------------|---------|-------------------------------|------------------------------------|---------|
| propan-2-ol | 67-63-0 | TWA                           | 400 ppm<br>999 mg/m <sup>3</sup>   | GB EH40 |
|             |         | STEL                          | 500 ppm<br>1.250 mg/m <sup>3</sup> | GB EH40 |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

##### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety glasses  
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Recommended: Butyl rubber/nitrile rubber gloves.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : No special environmental precautions required.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : white  
Odour : pleasant

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : 100 °C

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 3,5 - 5 (20 °C)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

---

### Viscosity

Viscosity, kinematic : > 7 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 23 hPa

Density : ca. 1,07 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): < 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

##### 2-methyl-2H-isothiazol-3-one (MIT):

Acute oral toxicity : LD50 (Rat): 200 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

##### Reproductive toxicity

Not classified based on available information.

##### STOT - single exposure

Not classified based on available information.

##### STOT - repeated exposure

Not classified based on available information.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### Aspiration hazard

Not classified based on available information.

### 11.2 Information on other hazards

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 9.714 mg/l  
aquatic invertebrates Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): >  
plants 100 mg/l  
Exposure time: 72 h

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic tox- : 100  
icity)

100

M-Factor (Chronic aquatic : 100  
toxicity)

100

##### **2-methyl-2H-isothiazol-3-one (MIT):**

M-Factor (Acute aquatic tox- : 10  
icity)

10

M-Factor (Chronic aquatic : 1  
toxicity)

1

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Com-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

pounds (OVOC)  
Volatile organic compounds (VOC) content: 1,6% w/w  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 1,6% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H301 : Toxic if swallowed.  
H310 : Fatal in contact with skin.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Corr. : Skin corrosion  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## SikaBond® PVA Wood Adhesive Ultra

Date of last issue: 03.06.2025  
Revision Date: 16.03.2026

Version 4.2

Print Date 16.03.2026

|                |                                                                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GB EH40        | : UK. EH40 WEL - Workplace Exposure Limits                                                                                                                                                                                             |
| GB EH40 / TWA  | : Long-term exposure limit (8-hour TWA reference period)                                                                                                                                                                               |
| GB EH40 / STEL | : Short-term exposure limit (15-minute reference period)                                                                                                                                                                               |
| ADR            | : European Agreement concerning the International Carriage of Dangerous Goods by Road                                                                                                                                                  |
| CAS            | : Chemical Abstracts Service                                                                                                                                                                                                           |
| DNEL           | : Derived no-effect level                                                                                                                                                                                                              |
| EC50           | : Half maximal effective concentration                                                                                                                                                                                                 |
| GHS            | : Globally Harmonized System                                                                                                                                                                                                           |
| IATA           | : International Air Transport Association                                                                                                                                                                                              |
| IMDG           | : International Maritime Code for Dangerous Goods                                                                                                                                                                                      |
| LD50           | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)                                                                                               |
| LC50           | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL         | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL            | : Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT            | : Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC           | : Predicted no effect concentration                                                                                                                                                                                                    |
| REACH          | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC           | : Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB           | : Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN