

SikaSeal® One Hour Caulk

DECLARATION OF PERFORMANCE

No. 33029261

| | | |
|----|--|---|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE: | 33029261 |
| 2 | INTENDED USE/S | Sealant for non-structural use in joints in buildings and pedestrian walkways part 1: Sealant for façade elements |
| 3 | MANUFACTURER: | Sika Services AG Tüffenwies 16-22 8064 Zürich |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | 4, 3 (reaction to fire) |
| 6a | DESIGNATED STANDARD: | BS EN15651-1: 2012 |
| | Conformity Assessment body/ies: | 0249 |

Declaration of Performance

SikaSeal® One Hour Caulk

33029261

2025/07 , ver. 01

1213

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Designated Technical Specification |
|---------------------------|-------------|------|------------------------------------|
| Reaction to fire | Class E | 3 | BS EN15651-1: 2012 |
| Loss of volume | ≤ 45 % | 4 | |
| Resistance to flow | ≤ 5 mm | 4 | |
| Elongation | ≥ 25 % | 4 | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 22 July 2025

Name : Alex West
Function: Head of Product Manager
At Leeds on 22 July 2025



End of information as required by UKCA

Declaration of Performance

SikaSeal® One Hour Caulk
33029261
2025/07 , ver. 01
1213



Sika Services AG, Zurich, Switzerland

DoP No. 33029261

BS EN 15651-1:2012

Conformity Assessment Body 0249

Sealant for non-structural use in joints in buildings and pedestrian walkways part 1: Sealant for façade elements

| | |
|--------------------|---------|
| Reaction to fire | Class E |
| Loss of volume | ≤ 45 % |
| Resistance to flow | ≤ 5 mm |
| Elongation | ≥ 25 % |
| | |
| | |
| | |
| | |
| | |
| | |

Sika.co.uk

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

SikaSeal® One Hour Caulk
33029261
2025/07 , ver. 01
1213

Declaration of Performance
SikaSeal® One Hour Caulk
33029261
2025/07 , ver. 01
1213

