



SikaMembran®-220 FR is a self-adhering fire retardant tape consisting of a butyl adhesive layer with a black aluminium foil outer layer which offers excellent waterproofing capability. It is designed for detailing around window and door openings, installed over the joint between the structure and incorporated units such as facade elements and windows to provide a secure and durable vapour barrier and waterproof seal. For ease of application, the rolls come with a split liner, positioned 30mm from the edge.

- Fire retardant tape, fire classification B-s1, d0*
- Easy, clean application
- Self-adhesive, with split liner
- Excellent adhesion to a wide variety of substrates
- Creates airtight and fire-safe detailing around the window and door frames.

For more information visit: www.sika.co.uk/facades

Our most current General Sales Conditions shall apply Please consult the most current local Product Data Sheet prior to any use







SIKA LIMITED

Head Office Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ United Kingdom

Contact

Phone +441707394444 E-Mail facades@uk.sika.com www.sika.co.uk/facades





PRODUCT INFORMATION	
Length	10m per roll
Width of roll	100mm to 500mm (in 50mm increments)
Thickness	1mm

*According to EN 13501-1:2018 applied onto substrate Euro class A2-s1, d0 or better with a minimal thickness of 12mm and a minimal density of 525 kg/m



BUILDING TRUST