

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sika® Primer-3 N

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent, Primer

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  <b>Response:</b> P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

ethyl acetate

### Additional Labelling

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 01-2119475103-46-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 40 - < 60
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 5 - < 10
propan-2-ol	67-63-0 200-661-7 01-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 5 - < 10
methanol	67-56-1 200-659-6 01-2119433307-44-XXXX	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370  specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %	< 1

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

dibutyltin dilaurate	77-58-7 201-039-8 01-2119496068-27-XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq 0,025 - < 0,25$
----------------------	---	---	-----------------------

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

Risks : irritant effects  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU
Further information: Indicative				
		TWA	200 ppm 734 mg/m3	2017/164/EU
		TWA	200 ppm 734 mg/m3	GB EH40
		STEL	400 ppm 1.468 mg/m3	GB EH40
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m3	2000/39/EC
		TWA	50 ppm 220 mg/m3	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm 441 mg/m3	GB EH40
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40
		STEL	500 ppm 1.250 mg/m3	GB EH40
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
Further information: Indicative, Identifies the possibility of significant uptake through the skin				
		TWA	200 ppm 266 mg/m3	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	250 ppm 333 mg/m3	GB EH40

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

##### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	methyl hippuric acid: 650 Millimoles per mole cre-	After shift	GB EH40 BAT

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

		atinine (Urine)		
--	--	--------------------	--	--

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
methanol	Workers	Skin contact		40 mg/m <sup>3</sup>
		Exposure time: 8 h		
	Consumers	Skin contact		260 mg/m <sup>3</sup>
		Exposure time: 8 h		

## 8.2 Exposure controls

### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Prevent product from entering drains.



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

If the product contaminates rivers and lakes or drains inform respective authorities.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : colourless

Odour : very faint

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : ca. -4 °C  
Method: closed cup

Auto-ignition temperature : 425 °C

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

#### Viscosity

Viscosity, dynamic : ca. 10 mPa.s (20 °C)

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

### Solubility(ies)

Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	99,9915 hPa
Density	:	ca. 0,98 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

###### ethyl acetate:

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

###### reaction mass of ethylbenzene and xylene:

- Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

###### propan-2-ol:

- Acute oral toxicity : LD50 Oral (Rat): < 5.000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

###### dibutyltin dilaurate:

- Acute oral toxicity : LD50 Oral (Rat): 2.071 mg/kg

##### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

###### Skin sensitisation

Not classified based on available information.

###### Respiratory sensitisation

Not classified based on available information.

###### Germ cell mutagenicity

Not classified based on available information.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **reaction mass of ethylbenzene and xylene:**

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia (water flea)

##### **propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 9.714 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

Toxicity to algae/aquatic plants : EC50 (*Scenedesmus capricornutum* (fresh water algae)): > 100 mg/l  
Exposure time: 72 h

### **dibutyltin dilaurate:**

Toxicity to fish : LC50 (Fish): 3,1 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia* (water flea)): 1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (*Selenastrum capricornutum* (green algae)): 1 - 10 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1866  
IMDG : UN 1866  
IATA : UN 1866

#### 14.2 UN proper shipping name

ADR : RESIN SOLUTION  
IMDG : RESIN SOLUTION  
IATA : Resin solution

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

**IATA** : 3

### 14.4 Packing group

#### ADR

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

#### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA (Passenger)

Environmentally hazardous : no

#### IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	dibutyltin dilaurate

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 66,3% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 66,6% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### Other regulations:

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H301	:	Toxic if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H341	:	Suspected of causing genetic defects.
H360FD	:	May damage fertility. May damage the unborn child.
H370	:	Causes damage to organs if swallowed.
H370	:	Causes damage to organs.
H372	:	Causes damage to organs through prolonged or repeated exposure if swallowed.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Muta.	:	Germ cell mutagenicity
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika® Primer-3 N

Date of last issue: 18.12.2023  
Revision Date: 19.01.2024

Version 9.6

Print Date 29.02.2024

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN