

Everbuild® 203 Accelerator & Frostproofer

DECLARATION OF PERFORMANCE No. 10906124

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	10906124
2	INTENDED USE/S	Hardening and accelerating admixture
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	Not Applicable
5	SYSTEM/S OF AVCP:	System 2+
6a	DESIGNATED STANDARD:	BS EN934-2:2009 +A1:2012
	Conformity Assessment body/ies:	0120

Declaration of Performance

Everbuild® 203 Accelerator & Frostproofer
10906124
2024/01 , ver. 02
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Chloride ion content	<0.1% w/w		BS EN934-2:2009
Alkali Content	<2% w/w		
Corrosion Behaviour	Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate		
Compressive Strength	>120% of control 20°C and 24 hours		
	>90% of control 20°C and 28 days		
	>130% of control 5°C and 48 hours		
Air Content in Fresh Concrete	≤2% by volume above control		
Dangerous Substances	None (see MSDS)		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product Co-ordinator
At Leeds on 24 January 2024

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 24 January 2024



End of information as required by Regulation

Declaration of Performance

Everbuild® 203 Accelerator & Frostproofers
10906124
2024/01, ver. 02
1213



21

Sika Services AG, Zurich, Switzerland

DoP No. 10906124

BS EN934-2:2009 +A1:2012

Conformity Assessment Body 0120

Hardening and accelerating admixture

Chloride ion content	<0.1% w/w
Alkali Content	<2% w/w
Corrosion Behaviour	Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate
Compressive Strength	>120% of control 20°C and 24 hours
	>90% of control 20°C and 28 days
	>130% of control 5°C and 48 hours
Air Content in Fresh Concrete	≤2% by volume above control
Dangerous Substances	None (see MSDS)

eclarations of Performance Downloads | Sika Limited

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Everbuild® 203 Accelerator & Frostproofers
10906124
2024/01, ver. 02
1213



Declaration of Performance

Everbuild® 203 Accelerator & Frostproofer
10906124
2024/01 , ver. 02
1213

