According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Revision Date: 15.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Plastiment®-190

UFI:

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat- H412: Harmful to aquatic life with long lasting ef-

egory 3 fee

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting ef-

fects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours. P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

triisobutyl phosphate 2-octyl-2H-isothiazole-3-one (OIT)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | Classification | Concentration |
|---------------------|---------------------|---------------------|----------------|
| | EC-No. | | (% w/w) |
| | Registration number | | |
| 2,2'-iminodiethanol | 111-42-2 | Acute Tox. 4; H302 | >= 0,1 - < 0,5 |
| | 203-868-0 | Skin Irrit. 2; H315 | |
| | 01-2119488930-28- | Eye Dam. 1; H318 | |
| | XXXX | STOT RE 2; H373 | |
| | | Repr. 2; H361fd | |

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

| triisobutyl phosphate | 126-71-6 204-798-3 01-2119957118-32- XXXX | Skin Sens. 1B; H317 | >= 0,1 - < 0,5 |
|------------------------------------|--|---|------------------------|
| 2-octyl-2H-isothiazole-3-one (OIT) | 26530-20-1 247-761-7 01-2120768921-45- XXXX | Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 | >= 0,0025 - < 0,025 |
| | | M-Factor (Acute aquatic toxicity): 100100 M-Factor (Chronic aquatic toxicity): 100100 | |
| | | specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % | |
| | | Acute toxicity esti- mate | |
| | | Acute oral toxicity: 125 mg/kg 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l | |
| | | 0,27 mg/l Acute dermal toxicity: 311 mg/kg 311 mg/kg | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eve wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

sensitising effects Risks

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Revision Date: 15.12.2023

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Revision Date: 15.12.2023

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Components | CAS-No. | Value type (Form | Control parame- | Basis * |
|------------|---------|------------------|-----------------|---------|
| | | of exposure) | ters * | |

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Version 4.1 Date of last issue: 08.03.2023 Print Date 29.02.2024

Revision Date: 15.12.2023

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour brown

Odour characteristic

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

per flammability limit

Upper explosion limit / Up- : No data available

Lower explosion limit /

Lower flammability limit

: No data available

Flash point Not applicable

Auto-ignition temperature No data available

Decomposition temperature No data available

pΗ ca. 8

Viscosity

Viscosity, kinematic < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility soluble

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Revision Date: 15.12.2023

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 23 hPa

Density : ca. 1,16 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Revision Date: 15.12.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

2-octyl-2H-isothiazole-3-one (OIT):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute toxicity estimate: 0,27 mg/l Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

: The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-iminodiethanol:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 55 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (green algae)): 75 mg/l

Exposure time: 72 h

triisobutyl phosphate:

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 11 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: IC50 (Desmodesmus subspicatus (green algae)): 34,1 mg/l

Exposure time: 72 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic tox- : 100 icity)

100

M-Factor (Chronic aquatic

toxicity)

100

100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Not applicable

Control of Major Accident Hazards Regulations Not applicable

2015 (COMAH)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed. H302 : Harmful if swallowed. H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H361fd : Suspected of damaging fertility. Suspected of damaging the

unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Repr. : Reproductive toxicity Skin Corr. : Skin corrosion Skin Irrit. : Skin sensitisation : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Plastiment®-190

Date of last issue: 08.03.2023 Version 4.1 Print Date 29.02.2024

Revision Date: 15.12.2023

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN