

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikadur®-31 + Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

	H318	Causes serious eye damage.
Precautionary statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	<b>Prevention:</b>	
	P261	Avoid breathing dust.
	P280	Wear protective gloves/ eye protection/ face protection.
	<b>Response:</b>	
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
	<b>Disposal:</b>	
	P501	Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8 234-148-4 01-2119970376-29-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317  Acute toxicity estimate  Acute oral toxicity: 1.669 mg/kg Acute dermal toxicity: 1.310 mg/kg	>= 5 - < 10
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12-XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5
Substances with a workplace exposure limit :			
Limestone Contains: Quartz (SiO <sub>2</sub> ) <5µm >= 0,1 %	1317-65-3 215-279-6		>= 25 - < 40
calcium carbonate	471-34-1 207-439-9 01-2119486795-18-XXXX		>= 5 - < 10

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects
- Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

Further information : Standard procedure for chemical fires.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40
<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>				
		TWA (Respirable dust)	4 mg/m3	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m3	GB EH40
<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>				
		TWA (Respirable dust)	4 mg/m3	GB EH40

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : solid  
Appearance : paste  
Colour : grey
- Odour : amine-like
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : > 101 °C  
Method: closed cup



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

Auto-ignition temperature : No data available

No data available

No data available

Decomposition temperature : No data available

pH : alkaline  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : ca. 400.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Density : ca. 1,81 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### **N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:**

Acute oral toxicity : LD50 Oral (Rat): 1.669 mg/kg

Acute toxicity estimate: 1.669 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 1.310 mg/kg

Acute toxicity estimate: 1.310 mg/kg  
Method: Calculation method

##### **Polyoxypropylene diamine:**

Acute oral toxicity : LD50 Oral (Rat): 2.880 mg/kg

##### **Skin corrosion/irritation**

Causes skin irritation.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

### Product:

Method : OECD Test Guideline 435  
Result : Skin irritation  
Remarks : Expert judgement

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

Not classified due to lack of data.

#### **STOT - repeated exposure**

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Polyoxypropylene diamine:**

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 80 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

##### Product:

Additional ecological information : There is no data available for this product.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

- ADR : Not regulated as a dangerous good

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Skin Corr. : Skin corrosion  
Skin Sens. : Skin sensitisation  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikadur®-31 + Part B

Date of last issue: 10.01.2024  
Revision Date: 10.01.2024

Version 2.1

Print Date 29.02.2024

LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GB / EN