

## PRODUCT DATA SHEET

# SikaWall®-5400 Exposed Aggregate

### EWI Dry Dash Receiver

#### PRODUCT DESCRIPTION

SikaWall®-5400 Exposed Aggregate is a factory batched polymer modified dry mix through coloured render. This product is used as a dry dash receiver on render only and a number of Sika insulation systems, this product only requires the addition of clean potable water; no other material should be added.

#### USES

As an EWI dry dash receiver.

#### PRODUCT INFORMATION

<b>Packaging</b>	25 kg bags
<b>Shelf Life</b>	12 Months from date of manufacture
<b>Storage Conditions</b>	Dry frost free conditions
<b>Consumption</b>	When applied to a correctly prepared even substrate at a thickness of 8-10 mm (recommended thickness). A 25 kg bag approximately covers 2 m <sup>2</sup> .

#### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### LIMITATIONS

- Product intended for professional use.
- It is advisable when completing the different finishes, to take into account the hardening time, which will vary according to climatic conditions.
- Avoid applications on substrates exposed to direct sun or in hot drying winds.
- Do not apply on over heated substrates. In hot conditions dampen the substrate prior to application. Dampen the render after application.

#### CHARACTERISTICS / ADVANTAGES

- Forms part of a number of accredited insulation systems.
- Suitable for one coat application.
- Suitable for Spray Application.
- Extended Workability.
- Available in range of natural colours, See Sales for colour charts and samples.
- Can be finished in a variety of Decorative Aggregates.

- Do not apply to a frozen substrate or on thawing substrates. Do not use in freezing conditions. Take precautions during damp climatic conditions. (Discolouration could occur).
- Do not apply on very wet substrates or where there are wet patches. (Discolouration could occur).
- Minimum application temperatures: +5 °C for light colours, +8 °C for dark colours.
- Over 30 °C, special precautions must be taken. In order to reduce the risk of colour differences after drying, always use the same batch number for the same façade

## ECOLOGY, HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye / face protection. This product contains materials which may cause an allergic reaction, is irritating to eyes and harmful if swallowed. In case of contact, seek medical advice. Keep out of the reach of children. Read and follow the guidelines in the Health and Safety data sheet for this product.

### SUBSTRATE QUALITY

Suitable Substrates

- SikaWall®-100 Base Coat.
- SikaWall®-1015 Coat.

Unsuitable Substrates

- Painted surfaces.
- Non polymer modified base coats.

### MIXING

MIXING

A 25 kg bag of SikaWall®-5400 Exposed Aggregate should be:

- Mixed with 5.5 L of clean potable water no other material should be added.
- Mixed by a concrete mixer or paddle mixer.
- Mix for approximately five minutes.
- Care should be taken not to over mix or over trowel.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
SikaWall®-5400 Exposed Aggregate  
April 2022, Version 01.01  
021830400400000015

SikaWall-5400ExposedAggregate-en-GB-(04-2022)-1-1.pdf