



# Sikafloor® Marine-190

## SELF-LEVELLING PRIMARY DECK COVERING

- Fast setting
- Non-combustible
- Ideal for refits
- Smooth surface for soft floor coverings

# Sikafloor® Marine-190

Sikafloor® Marine-190 is a one-component, fast setting self-levelling mortar based on polymer modified cement. It is mainly used for primary deck covering prior to the application of deck finishing materials such as carpets, tiles, parquet, rubber and vinyl.

For specific applications consult the product data sheet or contact your Sika Technical Service.

## PRODUCT BENEFITS

- Fast setting
- Simple application
- Non-combustible
- Pumpable
- Ideal for refits
- Excellent levelling properties
- Smooth surface for soft floor coverings
- Can be spike rolled

## AREAS OF APPLICATION

- Primary deck covering areas requiring a smooth surface
- Prior applications of carpets, vinyl, tiles, rubber, etc.
- Ideal for dry applications areas
- Lounges, dining rooms, corridors, cabinets, etc.
- Wet areas



## Typical Product Data

Color	Grey
Cure mechanism	Hydraulic
Mixing ratio with cold, potable water per 25 kg bag	5.3 - 5.8 liters (21-23%)
Density cured <sup>1</sup>	1.8 g/cm <sup>3</sup> approx.
Application thickness	3 - 25 mm
Coverage per 25 kg bag (layer thickness 1 mm)	13 m <sup>2</sup> approx.
Working time <sup>2</sup>	20 minutes approx.
Ready to walk on <sup>2</sup>	2 hours approx.
Compressive strength <sup>3</sup>	33 MPa approx.
Shelf life	9 months

<sup>1</sup> After 7 days

<sup>2</sup> 23°C / 50% r.h.

<sup>3</sup> After 28 days

Our most current General Sales Conditions shall apply. Please consult the Data Sheet prior to any use and processing.



## SIKA SERVICES AG

Tueffenwies 16  
8048 Zurich  
Switzerland

## CONTACT

Phone: +41 58 436 40 40  
Fax: +41 58 436 55 30  
[www.sika.com/marine](http://www.sika.com/marine)  
[www.sika.com/marine\\_innovations](http://www.sika.com/marine_innovations)

**BUILDING TRUST**

