

Sikatherm PIR AL

DECLARATION OF PERFORMANCE No. 11803665

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	11803665
2	INTENDED USE/S	BS EN 13165:2012+A2:2016 Thermal insulation products for buildings. Factory made rigid polyurethane foam (PU) products.
3	MANUFACTURER:	Sika Limited, Watchmead, Welwyn Garden City Hertfordshire, AL7 1BQ, United Kingdom.
5	SYSTEM/S OF AVCP:	System 3/4
6a	HARMONISED STANDARD:	BS EN 13165:2012+A2:2016
	Notified body/ies:	University of Salford :1145 Warrington Fire: 0833, BITS 1334
7	DECLARED PERFORMANCE/S:	

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Thermal resistance RD ((m ² .K)/W)	dN 30mm 0.95 dN 30mm 1.35 dN 40mm 1.80 dN 50mm 2.25 dN 60mm 2.70 dN 70mm 3.15 dN 80mm 3.60 dN 90mm 4.05 dN 100mm 4.50 dN 120mm 5.45 dN 130mm 5.90 dN 140mm 6.35 dN 150mm 6.80 dN 160mm 7.25	System 3	
Thermal conductivity λD (W/(m.K))	dN 20mm 0.022 dN 160mm 0.022	System 3	
Thickness tolerance	T2	System 3	
Reaction to fire	F	System 4	
Durability of reaction to fire against heat, weathering, ageing / degradation			
Durability of the reaction to fire of the product as placed on the market	NPD	System 3	BS EN 13165
Durability of thermal resistance and thermal conductivity against ageing/degradation	NPD	System 3	
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal conductivity λD (W/(m.K)) dN 0.022	System3	
Durability characteristics	NPD	System 3	
Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1	System 3	
Deformation under specified compressive load and temperature conditions	NPD	System 3	
Determination of the aged	λD 0.022 W/m·K	System 3	

Declaration of Performance

Sikatherm PIR AL
11803665 2022/2 VERS 2

Compressive stress or compressive strength	CS(10\Y)150	System 3	
Tensile / Flexural strength Tensile strength perpendicular to faces	TR40	System 3	
Durability of compressive strength against ageing / degradation Compressive creep	NPD	System 3	
Water permeability Short term water absorption	NPD	System 3	BS EN 13165
Long term water absorption	NPD	System 3	
Flatness after one sided wetting	NPD	System 3	
Water vapour permeability Water vapour transmission	NPD	System 3	
Acoustic absorption index Sound absorption	NPD	System 3	
Continuous Glowing Combustion	NPD	System 3	
Release of dangerous substances to the indoor environment Release of dangerous substances	NPD	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Dean Grady
Function: Senior Product Engineer
11th Feb 2022

Name : Alex Coward
Function: Head of Technical
11th Feb 2022




End of information as required by UKCA



Sika Limited

DoP No. 11803665

BS EN 13165:2012+A2:2016

Thermal insulation products for buildings. Factory made rigid polyurethane foam (PU) products.

Notified Body University of Salford :1145 Warrington Fire: 0833, BITS 1334

Thermal resistance RD ((m ² .K)/W)	dN 30mm 0.95 dN 30mm 1.35 dN 40mm 1.80 dN 50mm 2.25 dN 60mm 2.70 dN 70mm 3.15 dN 80mm 3.60 dN 90mm 4.05 dN 100mm 4.50 dN 120mm 5.45 dN 130mm 5.90 dN 140mm 6.35 dN 150mm 6.80 dN 160mm 7.25
Thermal conductivity λD (W/(m.K))	dN 20mm 0.022 dN 160mm 0.022
Thickness tolerance	T2
Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	
Durability of the reaction to fire of the product as placed on the market	NPD
Durability of thermal resistance and thermal conductivity against ageing/degradation	NPD
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal conductivity λD (W/(m.K)) dN 0.022
Durability characteristics	NPD

Declaration of Performance

Sikatherm PIR AL
11803665 2022/2 VERS 2

Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1
Deformation under specified compressive load and temperature conditions	NPD
Determination of the aged	λ D 0.022 W/m·K
Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength Tensile strength perpendicular to faces	TR40
Durability of compressive strength against ageing / degradation Compressive creep	NPD
Water permeability Short term water absorption	NPD
Long term water absorption	NPD
Flatness after one sided wetting	NPD
Water vapour permeability Water vapour transmission	NPD
Acoustic absorption index Sound absorption	NPD
Continuous Glowing Combustion	NPD
Release of dangerous substances to the indoor environment Release of dangerous substances	NPD

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikatherm PIR AL
11803665 2022/2 VERS 2