

BUILDING TRUST

PRODUCT DATA SHEET

Sikafloor®-001 Terrazzo Aggregate Mix

Natural Marble Aggregates for Terrazzo Flooring Systems

PRODUCT DESCRIPTION

Sikafloor®-001 Terrazzo Aggregate Mix consists of specifically graded marble, with a wide range of colours and sizes. The aggregates are pre-mixed to produce the optimum granulometry and colour(s) to obtain the defined standard formulations for the Sikafloor® Terrazzo EM-10 system when mixed with the Sikafloor® epoxy binder resin.

USES

Sikafloor®-001 Terrazzo Aggregate Mix is used to achieve a decorative effect in the Sikafloor® Terrazzo EM-10 system.

CHARACTERISTICS / ADVANTAGES

- Pre-mixed to achieve the optimum granulometry
- Washed and dried
- Available in a variety of colours and combinations
- Aesthetically pleasing
- Durable and hard-wearing

PRODUCT INFORMATION

Chemical Base	Natural aggregates
Packaging	25 kg bag
Shelf Life	5 years from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed-packaging in dry conditions at temperatures between +5 °C and +30 °C. Protect the Product from direct sunlight. Always refer to packaging.
Appearance / Colour	Natural marble chips Note: These aggregates are natural products and will vary in colour and shade.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling,

storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

IMPORTANT

Checking the Aggregates

Check the pre-mixed aggregates visually for consistency and quality before application.

Product Data Sheet

Sikafloor®-001 Terrazzo Aggregate Mix May 2024, Version 01.01 020816010010000114

IMPORTANT

Pre-mixing Aggregates

Premix a minimum of 4 bags of aggregates with a shovel or a machine before mixing the aggregates with the binder material. This is done to avoid an irregular appearance in the finished floor (i.e. produce a homogeneous finish).

IMPORTANT

Performing Pre-trials

Pre-trials / mock-up applications must be performed and procedures agreed with all parties before full project application.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet
Sikafloor®-001 Terrazzo Aggregate Mix
May 2024, Version 01.01
020816010010000114

