

## PRODUCT DATA SHEET

# Cromar® Flashing Strip Tape

Cromar® Flashing Tape is a self-adhesive bituminous sealing strip which bonds instantly to provide a watertight seal.

### PRODUCT DESCRIPTION

Cromar® Flashing Strip Tape is a self-adhesive polymer modified bitumen adhesive tape backed with a durable aluminum foil that creates a watertight seal on almost any surface. It is ready to use and ideal for sealing and repairing of metal sheeting, water tanks, downpipes and gutters.

A crease-resistant lead tape, this flashing tape is used for sealing and general repairs.

Cromar® Flashing Strip Tape has a heavy-duty aluminium/polyester laminate facing with a high-grade bitumen backing. This gives the product tear resistance, thus aiding speed and ease of application.

Cromar® Flashing Strip Tape bonds to most building materials including steel, aluminum, metals, concrete, stone, bricks, cement plaster, polycarbonate, PVC, glass, and wood and roofing felt.

### USES

- Repairing lead flashing.
- Sealing valley gutters.
- Repairing leaks in guttering and drainpipes.
- Protecting insulation for pipes and tanks.
- Repairs to greenhouses.
- Repairing roofing felt joints.

### CHARACTERISTICS / ADVANTAGES

- Instant water-tight seal—impermeable to moisture and water vapour.
- Quick effective repairs.
- Excellent resistance to weathering.
- Durable, remaining permanently flexible.
- Strong aluminum foil backing.

### PRODUCT INFORMATION

Packaging	Dimensions	Box Quantity
	50 mm x 10 m	6
	100 mm x 10 m	6
	150 mm x 10 m	4
	225 mm x 10 m	2
	300 mm x 10 m	2
	450 mm x 10 m	1
	600 mm x 10m	1

Colour	Grey		
Shelf Life	12 months		
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging, in dry conditions at temperatures between +10 °C and +40 °C.		
Dimensions	Characteristic	Units	Value
	Length	m	10
	Width	mm	50, 100, 150, 225, 300, 450, 600

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

- Not suited for polypropylene, polyethylene and Teflon.
- Not suitable for sealing high-pressure systems.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

All surfaces must be dry, sound and free from oil, grease and dust. Remove all loose material by scraper or wire brush. Porous surfaces, such as concrete or brick, should be primed using Cromar® Bitumen Primer and allowed to dry.

## APPLICATION

Cut to the required length. Peel back approximately 50 mm of release backing cover and place the tape into position. Continue removing the release backing whilst firmly placing the tape to avoid unnecessary creasing. Ensure intimate contact and that no air is trapped. Using a small roller ensure that all edges and overlaps are sealed properly. Overlaps should be at least 25 mm.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**SIKA LIMITED**  
Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

