

PRODUCT DATA SHEET

Cromar® Trim Adhesive

A single-component, moisture curing, polyurethane-based sealant.

PRODUCT DESCRIPTION

Cromar® Trim Adhesive is specifically formulated for bonding and sealing GRP roofing trims within the Cromar PRO GRP and Flexiglass roofing systems. It provides a strong, flexible and weather resistant bond, ensuring secure fixing and longterm performance of trims, fascias and edge details.

USES

- Bonding GRP edge trims, drip trims and fascia trims.
- Sealing corners, joints and upstands used in the PRO GRP and Flexiglass roofing systems.
- Fixing trims to common roofing substrates including:
 - Timber
 - Concrete
 - GRP
 - Metal

CHARACTERISTICS / ADVANTAGES

- Single component polyurethane formulation.
- Fast curing for efficient installation.
- High strength, elastic bond accommodates movement.
- Excellent adhesion to most common building substrates.
- Weather, UV and moisture resistant.

PRODUCT INFORMATION

Packaging	Pre-printed cartridges - 300 ml
Colour	Grey
Shelf Life	12 months
Storage Conditions	The product should be stored properly in original, unopened and undamaged packaging, in dry conditions at temperatures between + 5 °C and + 25 °C.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety

APPLICATION INSTRUCTIONS

- Apply using a standard sealant gun.
- Apply a continuous bead to the trim or substrate.
- Press trim firmly into position to ensure full contact.
- Remove excess material immediately.
- Allow to cure in accordance with ambient conditions, ideally + 5 °C to + 35 °C.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Cromar® Trim Adhesive
October 2026, Version 01.01
020915955000247380

CromarTrimAdhesive-en-GB-(10-2026)-1-1.pdf