

## PRODUCT DATA SHEET

## Sika® Tarmac Restorer

Restores tarmac to a deep black finish

## PRODUCT DESCRIPTION

Sika® Tarmac Restorer is a high performance, water-based surface coating designed to restore and enhance the appearance of faded or stained tarmac. Once dry Sika® Tarmac Restorer provides a tough, durable, low sheen finish which protects from weathering, oil and petrol spills and weed growth. Easy to apply and quick drying, most driveways can be used again within 4 hours.

## USES

- Tarmac driveways and paths.
- Private car parks.
- Residential and commercial surfaces.

## CHARACTERISTICS / ADVANTAGES

- Tough and long-lasting.
- Protects against common spills and plant / weed growth.
- Fast-drying.

## PRODUCT INFORMATION

Chemical Base	Water-based acrylic polymer
Packaging	5 L Jerry Can
Appearance / Colour	Black liquid
Shelf Life	12 months from date of manufacture when stored according to the manufacturer's instructions.
Storage Conditions	Store in original containers in cool dry conditions between +5 °C to +25 °C. Do not allow to freeze.
Density	0.9 - 1.1 g/cm <sup>3</sup>

## TECHNICAL INFORMATION

Chemical Resistance	Resistant to: most salt solutions, dilute acids and alkalis, water and limited oil. Not resistant to: solvents and some detergent solutions.
---------------------	---

## APPLICATION INFORMATION

Consumption	4 - 6 m <sup>2</sup> per litre depending on porosity of substrate.
Ambient Air Temperature	+5 °C to +35 °C. Surfaces must be free from ice and water.
Curing Time	4 - 6 hours depending on drying conditions.

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

- Do not use if ambient air or surface temperature is below +5 °C.
- Do not use if rain is imminent (within 6 hours).
- Do not use over fresh tarmac. Allow tarmac to dry for a minimum of 3 months prior to application.
- Do not subject to vehicular traffic within 4 hours of application.
- At lower temperatures drying times will be significantly extended. Always check surface is dry before trafficking.
- Oil, petrol or chemical spills should be removed from Sika® Tarmac Restorer as quickly as possible with warm water, detergent and a clean cloth.
- Do not use a high pressure spray to clean Sika® Tarmac Restorer.

It is the user's responsibility to determine suitability for use. If in any doubt contact Technical Services for advice.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

- All surfaces must be clean and free from dirt, algae, grease and any loose material.
- The surface may be damp, however any surface water/puddles must be removed.
- Use Sika® Oil Remover to remove any oil or grease spills.
- Lichen or surface mould can be removed using Sika® 404 Fungicidal Wash or Sika® Mouldbuster and cleaned using fresh water and a stiff bristle brush.
- Repair cracks or damaged areas before application.

## APPLICATION

- Stir well before and during use.
- Apply in dry weather with a brush or long pile roller in an even coat across the entire surface.
- Apply in 2 coats allowing 4 hours between coats.

## CLEANING OF TOOLS

Clean all equipment immediately after use with clean water and detergent.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

Sika® Tarmac Restorer  
September 2025, Version 01.01  
020816990010245242

SikaTarmacRestorer-en-GB-(09-2025)-1-1.pdf