

PROVISIONAL SYSTEM DATA SHEET

Sikafloor® MultiFlex PB-37

Slip-resistant, Tough-elastic Polyurethane Flooring System

PRODUCT DESCRIPTION

Sikafloor® MultiFlex PB-37 is a slip-resistant, tough-elastic polyurethane Flooring System. It is part of the Sikafloor® MultiFlex Flooring Range.

USES

Sikafloor® MultiFlex PB-37 may only be used by experienced professionals.

The System is used in industrial buildings such as:

- Car park decks
- Automotive facilities
- Logistics facilities and warehouses

Please note:

The System may only be used for interior applications.

SYSTEM INFORMATION

| System Structure | Layer | Product |
|--------------------------|-------------------------------------|--|
| | 1. Primer | Sikafloor®-150 Sikafloor®-151 Sikafloor®-1590 |
| | 2. Wearing Layer | Sikafloor® BC 375 N filled 1 : 0.3 with Quartz sand (0.1–0.3 mm) by weight Broadcast to excess with Quartz sand (0.3–0.8 mm) |
| | 3. Seal Coat | Sikafloor® BC 375 N |
| Composition | Polyurethane | |
| Appearance | Slip resistant, matt finish | |
| Colour | Available in various colour shades. | |
| Nominal thickness | ~2.0 mm | |

TECHNICAL INFORMATION

Provisional System Data Sheet
Sikafloor® MultiFlex PB-37
November 2024, Version 02.01
02081290000000135

THE PRODUCT DESCRIBED IN THIS PRODUCT DATA SHEET (PDS) IS STILL UNDER DEVELOPMENT AND HAS NEITHER BEEN FINALLY RELEASED NOR CERTIFIED. THIS PDS MUST NOT BE USED FOR THE APPLICATION OF THE PRODUCT. SIKA MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE PERFORMANCE, QUALITY OR OTHER CHARACTERISTICS OF THE PRODUCT.

| | | |
|---------------------------|--------------|--------------|
| Tensile adhesion strength | ≥ 1.5 MPa | (EN 1542) |
| Reaction to Fire | Class Bfl-s1 | (EN 13501-1) |

APPLICATION INFORMATION

| Consumption | Layer | Product | Consumption |
|-------------|----------------------------|--|--|
| | Primer | Sikafloor®-150 Sikafloor®-151 Sikafloor®-1590 | 1 to 2 × 0.3–0.5 kg/m ² |
| | Levelling (if required) | Sikafloor®-150 Sikafloor®-151 Sikafloor®-1590 | Refer to the individual Product Data Sheet. |
| | Wearing Level | Sikafloor® BC 375 N filled 1 : 0.3 with Quartz sand (0.1–0.3 mm) by weight Broadcast to excess with Quartz sand (0.3–0.8 mm) | 1 × 1.0 kg/m ² 1.5 kg/m ² |
| | Seal Coat | Sikafloor® BC 375 N | 1 × 0.7 kg/m ² |

Waiting Time / Overcoating When using Sikafloor®-1590, refer to the individual Product Data Sheet for specific information on waiting time to overcoating.

Before applying Sikafloor® BC 375 N over the primer, allow:

| Temperature | Minimum | Maximum |
|-------------|----------|---------|
| +10 °C | 17 hours | 4 days |
| +20 °C | 9 hours | 2 days |
| +30 °C | 7 hours | 1 day |

Before applying Sikafloor® BC 375 N on Sikafloor® BC 375 N allow:

| Temperature | Minimum | Maximum |
|-------------|----------|----------|
| +10 °C | 24 hours | 3 days |
| +20 °C | 12 hours | 48 hours |
| +30 °C | 8 hours | 36 hours |

NOTE: Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.

| Applied Product Ready for Use | Temperature | Foot Traffic | Light Traffic | Full Cure |
|-------------------------------|-------------|--------------|---------------|-----------|
| | +10 °C | 72 hours | 6 days | 10 days |
| | +20 °C | 24 hours | 4 days | 7 days |
| | +30 °C | 18 hours | 2 days | 5 days |

NOTE: Times apply when the last layer of the System has been applied. Times are affected by changing ambient conditions, particularly temperature and relative humidity.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

Refer to the following Method Statements:

- Sika® Method Statement — Evaluation and Preparation of Surfaces for Flooring Systems.
- Sika® Method Statement — Sikafloor® Mixing and Application.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the

European Chemicals Agency in concentrations above 0,1 % (w/w).

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Provisional System Data Sheet
Sikafloor® MultiFlex PB-37
November 2024, Version 02.01
020812900000000135

PROVISIONAL_SikafloorMultiFlexPB-37-en-GB-(11-2024)-2-1.pdf