

## PRODUCT DATA SHEET

# Cromar® 90 Degree Top Closure

A preformed GRP Valley Trough.

### PRODUCT DESCRIPTION

The 90° Top Closure GRP Valley Trough is a factory manufactured, prefabricated drainage component designed for installation at the intersection of two valley trough runs forming a right-angle change in direction.

### USES

- Roof valley drainage systems.
- Industrial, commercial and infrastructure buildings.
- Flat and pitched roof interfaces with internal or external valley troughs.
- New-build and refurbishment projects.

### CHARACTERISTICS / ADVANTAGES

- 90° factory formed unit for accurate alignment and ease of installation.
- Top closure design to improve water tightness and reduce leak risk.
- Manufactured from GRP for high strength to weight ratio.
- Corrosion and weather resistant, suitable for longterm external exposure.
- Smooth internal surface to promote efficient water flow and minimise debris buildup.
- Low maintenance with long service life.

### PRODUCT INFORMATION

Packaging	Cardboard boxes containing 10 units.
Shelf Life	A preformed GRP item with no specific shelf life.
Storage Conditions	Store in cool, dry place, away from direct sunlight.

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

### ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very

### APPLICATION INSTRUCTIONS

- Designed for straightforward integration with standard GRP valley trough sections.
- Capable of being bonded, sealed, or mechanically fixed in accordance with project specification.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application

fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**SIKA LIMITED**  
Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



**Product Data Sheet**  
Cromar® 90 Degree Top Closure  
February 2026, Version 01.01  
020945201000247183

Cromar90DegreeTopClosure-en-GB-(02-2026)-1-1.pdf

**BUILDING TRUST**

