

PRODUCT DATA SHEET

EVERBUILD® Shed & Fence Mate

Water based shed and fence treatment

PRODUCT DESCRIPTION

EVERBUILD® Shed & Fence Mate is an easy to use, water based shed and fence treatment specifically designed to provide a safe alternative to creosote without the associated hazards. The product provides a durable water repellent finish to all rough sawn timber. EVERBUILD® Shed & Fence Mate contains carefully selected UV resistant pigments and water repellent waxes that makes the colour last up to six times longer than creosote. It is designed for use on all rough sawn garden timber including sheds, fences, gates, hutches, kennels, cold frames and trellises.

USES

Decorating and protecting all rough sawn timber.

CHARACTERISTICS / ADVANTAGES

- Water based formulation - non-flammable, low odour.
- Easy to use – water clean up of spills and tools.
- Water repellent – special waxes shed water for increased durability.
- Long lasting finish.
- Will cover existing creosote providing it has weathered, i.e. it isn't water repellent.

| | |
|--------------------|-----------|
| MFFT | 5°C |
| Drying Time | 2-6 Hours |

PRODUCT INFORMATION

| | |
|----------------------------|--|
| Packaging | 5L Plastic Bucket |
| Appearance / Colour | Coloured solution (water based) Country Oak, Burnt Oak, Rustic Red, Holly Green, Ebony Black. |
| Shelf Life | 24 months from date of manufacture when stored according to manufacturer's instructions. |
| Storage Conditions | Store at moderate temperatures, 5 - 30°C, in original containers. PROTECT FROM FROST. |
| Density | ~1.0 g/cm ³ |

APPLICATION INFORMATION

| | |
|--------------|--|
| Yield | 1 litre will cover approximately 6-12m ² per coat depending on nature of surface. |
|--------------|--|

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Surfaces must be free from grease, dust, loose material, moss, algae etc. Clean surfaces with EVERBUILD FUNGICIDAL WASH and use a wire brush for areas badly affected.

APPLICATION

Always stir well before use. Brush uniformly onto surface ensuring an even coverage. One coat is normally sufficient, but on some very porous or bare timbers, two or three coats may be required to achieve the correct depth of colour. Allow the first coat to dry before applying the second.

Drying time will be 2-6 hours depending on temperature. Do not apply below 5°C.

CLEANING OF TOOLS

Clean brushes, spillages etc in warm soapy water.

LIMITATIONS

- Use only as directed. Store only in original container.
- Use only on rough sawn, never planed timber.
- This product will cover existing creosote and other protective wood coating providing they are sufficiently weathered (i.e. non-water repellent).
- Do not use if rain is imminent (within 6 hours at 20°C).
- Do not apply below 5°C (air or surface temp).
- Always keep container upright and secure at all times during storage and transit.
- Dispose of this product and packaging correctly. Do not allow to enter watercourses. It is the users responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

Product Data Sheet

EVERBUILD® Shed &
Fence Mate

April 2018, Version
01.01

02199910000000074

2 / 2



BUILDING TRUST

