

## PRODUCT DATA SHEET

## SikaRoof® Tape P

Polyacrylate adhesive tape for Sarnafil® and Sikaplan® roof membranes

## PRODUCT DESCRIPTION

SikaRoof® Tape P is a polyacrylate double-sided adhesive tape used with Sarnafil® and Sikaplan® roof membranes.

## USES

SikaRoof® Tape P may only be used by experienced professionals.

- Bonds Sarnafil® T, Sarnafil® AT and Sikaplan® T roofing membranes to a range of upstand substrates

## CHARACTERISTICS / ADVANTAGES

- High tack and long-term adhesion
- Finger-lift release liner
- Contains no halogen or heavy-metal compounds
- Easily applied

## PRODUCT INFORMATION

Chemical Base	Adhesive Carrier	Polyester
	Adhesive	Polyacrylate
	Release liner	Siliconised PP
Packaging	4 rolls in a box Refer to current price list for packaging variations	
Appearance / Colour	Colourless	
Shelf Life	18 months from date of production	
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.	
Length	25,00 m (±0,5 m)	
Width	115 mm (±5 mm)	
Thickness	Overall 0,50 mm (±0,05 mm)	
Weight	1700 g (± 100 g) per roll	

## TECHNICAL INFORMATION

Elongation at Break	15–25 %	(EN 14410)
---------------------	---------	------------

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	Condition tape in application environment temperature before applying. Min. +5 °C / max. +40 °C
<b>Substrate Temperature</b>	+5 °C min. / +40 °C max.

## SYSTEM INFORMATION

<b>System Structure</b>	Compatible system products: <ul style="list-style-type: none"> <li>▪ Sarnafil® T and Sarnafil® AT roofing membranes</li> <li>▪ Sikaplan® T roofing membranes</li> </ul> Ancillary products: <ul style="list-style-type: none"> <li>▪ Primer-780</li> </ul>
<b>Compatibility</b>	Not compatible in direct contact with tar, asphalt, hot bitumen, PVC-P, wood preservatives with surfactants and substances containing oil, solvents or wetting agents. These materials could adversely affect the product properties.

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of SikaRoof® Tape P is limited to geographical locations with average monthly minimum temperatures of -20 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Not suitable for permanent exposure to weathering.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The substrate must be structurally sound, surface must be dry, clean and free of all contaminants such as dust, dirt, oil, grease and poorly bonded paint coatings which could affect adhesion.

The Following substrates are suitable for bonding: Oriented strand boards (OSB), plywood, smooth concrete, expanded polystyrene (EPS), extruded polystyrene (XPS), metal, polypropylene (PP), polyurethane (PUR) and polyisocyanurate (PIR) boards (aluminium and glass tissue faced)

### SUBSTRATE PREPARATION

All dust, loose and friable material must be completely removed from all surfaces before application of the tape. Porous substrates must be primed with Primer-780 (Refer to Product Data Sheet) before application of the tape.

### APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Horizontal application for upstand height < 300 mm.  
Vertical application for upstand height > 300 mm with a spacing of ~300 mm.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

SikaRoof® Tape P

August 2025, Version 01.01  
020945051200000013

SikaRoofTapeP-en-GB-(08-2025)-1-1.pdf