

PRODUCT DATA SHEET

Everbuild Tecnic[®] Sealant Primer P1

Sealant primer for use on porous surfaces

PRODUCT DESCRIPTION

Everbuild Tecnic[®] Sealant Primer P1 is a solvent based, acrylate-silicone copolymer primer for use on porous surfaces prior to applying all common types of silicone, polyurethane and hybrid sealants.

USES

For use on:

- Brick
- Stone
- Concrete
- Blockwork
- Floor screeds
- Render

CHARACTERISTICS / ADVANTAGES

- Works on most common porous building materials.
- Acts as a primer for dusty screeds.
- Works with all common silicone types.
- Can also be used with PU and hybrid based sealants.

Odour	Armomatic
Boiling Point	111°C
Working Temperature	5 to 40°C
Drying Time @ 20°C	Approx 30 minutes

PRODUCT INFORMATION

Packaging	1ltr tins
Appearance / Colour	Clear liquid
Shelf Life	12 months from date of manufacture. In original, unopened containers.
Storage Conditions	Store in cool, dry conditions between +5 and +25°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life. Opened tins must be closed airtight and used up as soon as possible (within 1 month).
Density	0.9 - 1g/cm ³
Flash Point	8°C

APPLICATION INFORMATION

Consumption	Coverage will vary according to type and porosity of substrate. As a guide, a 1ltr bottle will cover approx 2.5m ² .
--------------------	---------------------------------------------------------------------------------------------------------------------------------

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Apply by brush in one coat and allow to dry.

LIMITATIONS

- Do not use against bitumen or substrates that bleed oil or plasticisers.
- Do not use below +5°C.
- Do not apply to damp or wet surfaces.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Everbuild Tecnic®
Sealant Primer P1
February 2018,
Version 01.01
020516010000000040
2 / 2



EverbuildTecnicSealantPrimerP1-en-GBEVER-(02-2018)-1-1.pdf

BUILDING TRUST

