

PRODUCT DATA SHEET

SikaInject® AC-20 DE

Formerly TPH.® PUR-O-STOP FS-C / multi-product catalyst for polyurethane resins

PRODUCT DESCRIPTION

SikaInject® AC-20 DE is an accelerator for various Sika Injection Resins based on polyurethane, such as: SikaInject®-201 DE, SikaInject®-210 DE, SikaInject®-216 DE, further on request

USES

SikaInject® AC-20 DE may only be used by experienced professionals.

Accelerates the base resin where short potlife is needed, e.g.

- in flowing water applications
- in cold season
- in cold water applications

CHARACTERISTICS / ADVANTAGES

Only one accelerator for various SikaInject®-PU

- Shortens potlife
- Increase of efficiency
- Reduction of product loss, e.g. in flowing water

APPROVALS / STANDARDS

German General Building Inspectorate Approval for curtain grouting, AbZ, DIBT Berlin

PRODUCT INFORMATION

Packaging	4.5 kg / larger packaging on request
Colour	Colourless liquid
Shelf Life	12 months from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperature between +15 °C and +25 °C.
Density	~1.03 kg/L (DIN EN ISO 2811-1)
Viscosity	~120 mPas (DIN EN ISO 2555)

APPLICATION INFORMATION

Mixing Ratio	Measure and add small quantities of SikaInject® AC-20 DE into part A of the respective SikaInject®-PU Injection Resin and mix homogeneously (no streaks). The exact quantity (potlife table) can be found in the Product Data Sheet of the referring injection resin.
--------------	---

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaInject® AC-20 DE
February 2026, Version 01.01
02070701002000057

SikaInjectAC-20DE-en-GB-(02-2026)-1-1.pdf