

## PRODUCT DATA SHEET

# Cromar<sup>®</sup> Jointing Bandage

Glass Fibre Jointing Bandage.

### PRODUCT DESCRIPTION

The Cromar<sup>®</sup> Jointing Bandage is used to tape joints and seams on liquid roof system applications. The strands of the glassfibre are held together by an emulsion binder to form a mat.

### USES

- Reinforcement of joints and laps in liquid roofing systems before full lamination.
- Strengthening stress points such as around roof penetrations, trims, upstands, and edges.
- Crack bridging on roofs, gutters, flashings, and general waterproofing applications.
- Localised patch repairs on damaged areas prior to overcoating.
- Bridging gaps between dissimilar materials (e.g., metal to bitumen, GRP to concrete).
- Detailing work where additional layer strength is required to prevent resin shrinkage or surface cracking.

### PRODUCT INFORMATION

<b>Packaging</b>	10 rolls per cardboard box
<b>Shelf Life</b>	12 months
<b>Storage Conditions</b>	<ul style="list-style-type: none"><li>▪ Store dry, away from moisture and contamination.</li><li>▪ Keep in a cool, shaded environment, ideally +5 °C to +25 °C.</li><li>▪ Protect from UV exposure, which can weaken glass fibre binders over time.</li><li>▪ Keep the roll wrapped to avoid fraying and dust accumulation.</li></ul>
<b>Dimensions</b>	100 mm x 75 m

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### CHARACTERISTICS / ADVANTAGES

- High-strength woven glass fibre mat designed for reinforcement.
- Excellent tensile strength for bridging cracks, gaps, and joints.
- Flexible and conformable, allowing it to follow complex contours and irregular surfaces.
- Improves system durability by reinforcing weak points and preventing future movement or cracking.
- Easy to cut and handle for on-site application.

### LIMITATIONS

- Not a standalone waterproofing membrane - must always be embedded into a compatible liquid resin or coating system.
- Not suitable for structural reinforcement where

load-bearing strength is required.

- Must not be applied to damp, wet, oily, or contaminated substrates as adhesion of the coating system will be compromised.
- Not designed for use with solvent systems that may degrade binder coatings unless compatibility is confirmed.
- Unsuitable for areas subject to extreme movement without additional reinforcement layers.
- Should not be left exposed - must be fully encapsulated within resin/coating for durability.
- Not recommended for temperatures below +5°C during installation, as resin curing may be affected.
- Avoid use on friable or unsound substrates unless stabilised first.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

- Ensure substrate is clean, dry, and sound before installation.
- Cut Cromar® Jointing Bandage to size using scissors or a sharp blade.
- Apply the first coat of compatible resin or coating to the surface at the required coverage rate.
- Embed the bandage directly into the wet resin while still tacky.
- Smooth out to eliminate creases, folds, or trapped air pockets.
- Overlap bandage edges by at least 50 mm for continuity of reinforcement.
- Apply a second coat of resin/coating immediately to fully encapsulate the scrim.
- Allow to cure fully before applying any additional layers or topcoats.
- Protect from rain, frost, and contamination during curing.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
Cromar® Jointing Bandage  
March 2026, Version 01.01  
020915955000247266

CromarJointingBandage-en-GB-(03-2026)-1-1.pdf