

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-612 Purform®

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Signal word	:	Danger	
Hazard statements	:	H226 H304 H317 H412	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 P261 P280 Response: P301 + P310 P331 P370 + P378	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist or vapours. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hydrocarbons, C9, aromatics
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate
aromatic polyisocyanate
4-morpholinecarbaldehyde
m-tolyldiene diisocyanate

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35-XXXX [corresponding group CAS 64742-95-6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	59719-67-4 261-879-6 UK-01-6693092877-6-0001	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
aromatic polyisocyanate	53317-61-6 Not Assigned	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 2,5
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12-XXXX	Skin Sens. 1; H317	>= 0,1 - < 0,5

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

m-tolyldiene diisocyanate	26471-62-5 247-722-4 01-2119454791-34-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation toxicity (vapour): 0,107 mg/l	>= 0,0025 - < 0,025
Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.
Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).
sensitising effects

May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
m-tolylidene diisocyanate	26471-62-5	TWA	0,02 mg/m ³ (NCO)	GB EH40
	Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is rea-			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

	sonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.			
	STEL	0,07 mg/m3 (NCO)	GB EH40	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
m-tolylidene diisocyanate	26471-62-5	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	Workers	Inhalation	Long-term systemic effects	29,4 mg/m3
	Workers	Skin contact	Long-term systemic effects	16,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	6,25 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	Fresh water	0,0186 mg/l
	Marine water	0,00186 mg/l
	Fresh water sediment	0,709 mg/kg
	Marine sediment	0,0709 mg/kg
	Soil	1,131 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Colour : white

Odour : solvent-like

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 0,8 %(V)

Flash point : ca. 51 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : No data available

Viscosity

Viscosity, dynamic : ca. 900 - 4.000 mPa.s (20 °C)

Viscosity, kinematic : > 7 mm²/s (40 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 4,9996 hPa

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Density : ca. 1,39 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

aromatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

m-tolyldiene diisocyanate:

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute toxicity estimate: 0,107 mg/l
Test atmosphere: vapour
Method: Calculation method

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l
Exposure time: 72 h

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 87,1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 18,6 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

Country GB 100000034291

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

ADR : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA (Passenger)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

2015 (COMAH)

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 19,3% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 19,3% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H351	:	Suspected of causing cancer.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sikalastic®-612 Purform®

Date of last issue: 19.07.2023
Revision Date: 19.12.2023

Version 5.0

Print Date 29.02.2024

PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GB / EN