

PRODUCT DATA SHEET

Cromar® ProRidge Plus

Ridge kit for mortar-free applications.

PRODUCT DESCRIPTION

The Cromar® ProRidge Plus is a dry-fix roofing kit designed for ridge and hip applications. It provides a fast, mortar-free installation suitable for most ridge tiles and all-weather fixing.

USES

- Universal ridge system for pitched roofs
- Suitable for new builds and refurbishments
- For ridge tile mechanical fixing

PRODUCT INFORMATION

Packaging

Cardboard box containing;
Cromar® ProRidge Plus
6 m ventilated ridge roll
10 ridge brackets
20 ridge union seals
20 fixing screws
20 clamping plates
40 ridge union clips

Shelf Life

24 months

Storage Conditions

Store in cool, dry place, avoiding direct sunlight.

CHARACTERISTICS / ADVANTAGES

- Dry fixing – installation possible in all weather conditions.
- Universal compatibility – fits most ridge tile applications.
- Perforated roll for ventilation – helps reduce condensation.
- Vapour permeable, wind and rain resistant.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable condi-

tions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Unroll the Cromar® ProRidge Plus, nail/staple every 300 mm with min. 75 mm side overlap.
- Remove adhesive backing and bond the butyl strip to the tiles.
- Screw the union clips and clamps in place prior to placing ridge tile.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® ProRidge Plus
March 2026, Version 01.01
020945201000263155

CromarProRidgePlus-en-GB-(03-2026)-1-1.pdf