

## PRODUCT DATA SHEET

# Cromar<sup>®</sup> Raised Angle Trim

Angle trim for the Cromar<sup>®</sup> PRO GRP and Flexiglass liquid roof systems.

### PRODUCT DESCRIPTION

The Cromar<sup>®</sup> Raised Angle Trim is a rigid GRP (glass reinforced polyester) edge profile designed to provide a secure, weatherproof upstand at the perimeter of flat roofing systems. It forms a clean, defined edge that prevents water run-off while directing surface water back into the roof area towards the intended drainage points.

### USES

- 105 mm vertical upstand provides a defined raised edge to contain water on flat roofs.
- Manufactured from durable GRP, offering excellent weathering, UV resistance, and dimensional stability.
- Lightweight but rigid profile designed to maintain shape and resist impact over time.
- Clean, professional finish with smooth edges and uniform thickness.
- Pre-formed corners and jointing pieces available for fast, consistent detailing.
- Can be easily trimmed and fixed on-site with standard tools.

### CHARACTERISTICS / ADVANTAGES

- Consistent weight and thickness.
- Excellent finish and appearance.
- High strength and flexibility.
- Excellent long-term durability.
- Easy jointing.
- Facilitates roof void ventilation.
- Unique high adhesion finish.

### PRODUCT INFORMATION

<b>Packaging</b>	Banded in 10 lengths of 3 m
<b>Shelf Life</b>	Shelf life has not been determined due to the longevity of plastic items.
<b>Storage Conditions</b>	The product must be stored properly in undamaged sealed packaging, in dry conditions at temperatures between +5 °C and +30 °C.
<b>Dimensions</b>	105 mm x 85 mm
<b>Length</b>	3 m

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

This trim is for use against an abutting wall or parapet. Place the trim against the wall making sure it sits squarely. Fix in place to decking, not to the wall, using ring shank nails, at 150-200 mm centres.

Where the Cromar® Raised Angle Trim needs to be joined by overlapping, use a bead of trim adhesive across the full width of the trim. For a cleaner line a "soaker" can be used. The whole join should then be bandaged, sealing both trims together. If the roof is to be left overnight without a flashing trim in place, a bead of adhesive should be used to seal the top edge of the trim to the wall, sealing the open point. The main flat area of the roof should be covered with a tarpaulin.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
Cromar® Raised Angle Trim  
March 2026, Version 01.01  
020915955000247640

CromarRaisedAngleTrim-en-GB-(03-2026)-1-1.pdf