



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sikafloor®-15 Pronto

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Flooring system.

### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire AL7 1BQ  
United Kingdom

Telephone : +44 (0)1707394444

### 1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Sensitising	R43: May cause sensitisation by skin contact.
Irritant	R37/38: Irritating to respiratory system and skin.

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikafloor®-15 Pronto**



Revision Date 07.08.2014

Print Date 07.08.2014

Dangerous for the environment

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H225  
H315  
H317  
H335  
H412

Highly flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May cause respiratory irritation.  
Harmful to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273

Avoid release to the environment.

**Response:**

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 201-297-1 methyl methacrylate
- 203-080-7 2-ethylhexyl acrylate
- 500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight  $\leq$  700)

### Additional Labelling:

Contains epoxy constituents. May produce an allergic reaction.

## 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).  
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).



### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
methyl methacrylate 80-62-6 201-297-1	F; R11 Xi; R37/38 R43	Flam. Liq.2; H225 STOT SE3; H335 Skin Irrit.2; H315 Skin Sens.1; H317	>= 25 - < 50
2-ethylhexyl acrylate 103-11-7 203-080-7	Xi; R37/38 R43	STOT SE3; H335 Skin Irrit.2; H315 Skin Sens.1; H317	>= 20 - < 25
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (num- ber average molecular weight <= 700) 25068-38-6 500-033-5 01-2119456619-26-XXXX	Xi; R36/38 R43 N; R51/53	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 1 - < 2,5
1,1'-(p-tolylimino)dipropan-2-ol 38668-48-3 254-075-1	T; R25 R52/53	Acute Tox.3; H301 Aquatic Chronic3; H412	>= 1 - < 2,5

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
 Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
 Wash off with soap and plenty of water.  
 If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.



Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough  
Respiratory disorder  
Allergic reactions  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical
- Unsuitable extinguishing media : Water, High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.



Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.



Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : No data available

---

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm 208 mg/m3	GB EH40
		STEL	100 ppm 416 mg/m3	GB EH40
		TWA	50 ppm	2009/161/EU
		STEL	100 ppm	2009/161/EU

**8.2 Exposure controls**

**Personal protective equipment**

Eye protection : Safety glasses with side-shields  
 Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
 Butyl rubber/nitrile rubber gloves (0,4 mm),  
 Contaminated gloves should be removed.  
 Suitable for permanent exposure:  
 Viton gloves (0.4 mm),  
 breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated



exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: light yellow
Odour	: unpleasant
Odour Threshold	: No data available
Flash point	: ca. 10 °C
Autoignition temperature	: ca. 245 °C
Lower explosion limit	: 0 %(V)
Upper explosion limit	: 12,5 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: Note: not determined
Melting point/range	: ca. -48 °C
Boiling point/boiling range	: ca. 100 °C
Vapour pressure	: ca.38,7 hPa at 20 °C



Density	:	ca.1 g/cm <sup>3</sup> at 20 °C
Water solubility	:	Note: insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity, dynamic	:	ca.1.000 mPa.s at 20 °C
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available
Self-heating	:	, no

#### 9.2 Other information

No data available

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity



SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikafloor®-15 Pronto**



Revision Date 07.08.2014

Print Date 07.08.2014

**Components:**

**reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700) :**

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: > 20.000 mg/kg

**Skin corrosion/irritation**

**Product**

Causes skin irritation.

**Serious eye damage/eye irritation**

**Product**

No data available

**Respiratory or skin sensitisation**

**Product**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

**Product**

Mutagenicity : No data available

**Carcinogenicity**

**Product**

Carcinogenicity : No data available

**Reproductive Toxicity/Fertility**

Reproductive toxicity : No data available

No data available

**Reproductive Toxicity/Development/Teratogenicity**

Teratogenicity : No data available

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**



No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances



---

## SECTION 14: Transport information

### ADR

<b>14.1 UN number</b>	: 1247
<b>14.2 Description of the goods</b>	: METHYL METHACRYLATE MONOMER, STABILIZED
<b>14.3 Class</b>	: 3
<b>14.4 Packing group</b>	: II
Classification Code	: F1
Labels	: 3
Tunnel restriction code	: (D/E)
<b>14.5 Environmentally hazardous</b>	: no

### IATA

<b>14.1 UN number</b>	: 1247
<b>14.2 Description of the goods</b>	: Methyl methacrylate monomer, stabilized
<b>14.3 Class</b>	: 3
<b>14.4 Packing group</b>	: II
Labels	: 3
<b>14.5 Environmentally hazardous</b>	: no

### IMDG

<b>14.1 UN number</b>	: 1247
<b>14.2 Description of the goods</b>	: METHYL METHACRYLATE, MONOMER, STABILIZED
<b>14.3 Class</b>	: 3
<b>14.4 Packing group</b>	: II
Labels	: 3
EmS Number 1	: F-E
EmS Number 2	: S-D
<b>14.5 Marine pollutant</b>	: no

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikafloor®-15 Pronto**



Revision Date 07.08.2014

Print Date 07.08.2014



Highly flammable



Irritant

R-phrases : R11 Highly flammable.  
R37/38 Irritating to respiratory system and skin.  
R43 May cause sensitisation by skin contact.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases : S24 Avoid contact with skin.  
S37 Wear suitable gloves.

Hazardous components which must be listed on the label:

- 201-297-1 methyl methacrylate
- 203-080-7 2-ethylhexyl acrylate
- 500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight  $\leq$  700)

Special labelling of certain mixtures : Contains epoxy constituents. See information supplied by the manufacturer.

**Prohibition/Restriction**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed ( $\Rightarrow$  0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002  
Control of Substances Hazardous to Health Regulations 2002  
The Management of Health and Safety at Work Regulations



1999  
Health and Safety at Work Act 1974  
Environmental Protection Act 1990 & Subsidiary Regulations

## 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

---

## SECTION 16: Other information

### Full text of R-Phrases

R11	Highly flammable.
R25	Toxic if swallowed.
R36/38	Irritating to eyes and skin.
R37/38	Irritating to respiratory system and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Full text of H-Statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

|| Changes as compared to previous version !

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikafloor®-15 Pronto**



Revision Date 07.08.2014

Print Date 07.08.2014

---