

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** ADEKIT A 130 RESIN (A)
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Epoxy resin adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIKA AUTOMOTIVE FRANCE SAS
15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE
Tél. +33 (0)1 34 40 34 60
- **Further information obtainable from:** DPT HSE - +33 (0)1 34 40 34 60 - safety@fr.sika.com
- **1.4 Emergency telephone number:**
ORFILA : +33 (0)1 45 42 59 59
+44 (0)1707 363899 (available during office hours).

*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07 GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
bis-[4-(2,3-epoxipropoxy)phenyl]propane
- **Hazard statements**
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H317 May cause an allergic skin reaction.
 - H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P264 Wash thoroughly after handling.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves / eye protection / face protection.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P391 Collect spillage.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 13.11.2020

Version number 8

Revision: 13.11.2020

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment** Not applicable.

*

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	50-100%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119456619-26		

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCl)

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

- **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 3)

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 2)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves

- **Material of gloves**

Synthetic rubber gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

GB

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 3)

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Viscous

Colour: Yellow

· **Odour:** Characteristic

· **Change in condition**

Melting point/freezing point: NA °C

Initial boiling point and boiling range: >200 °C (DIN 53171)

· **Flash point:** >110 °C (ISO 2719)

· **Ignition temperature:** >300 °C (DIN 51 794)

· **Decomposition temperature:** >200 °C (DIN 53171)

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Density at 25 °C:** 1.15 g/cm³ (ISO 1675:1985)

· **Solubility in / Miscibility with water:** Insoluble.

· **organic solvents:** Soluble in many organic solvents.

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

May produce violent reactions with bases and numerous organic substances including alcohols and amines.
Exothermic polymerisation.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 13.11.2020

Version number 8

Revision: 13.11.2020

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 4)

- **10.6 Hazardous decomposition products:** Irritant gases/vapours

*	SECTION 11: Toxicological information							
	<ul style="list-style-type: none"> · 11.1 Information on toxicological effects · Acute toxicity Based on available data, the classification criteria are not met. 							
	<ul style="list-style-type: none"> · LD/LC50 values relevant for classification: 							
	<p>1675-54-3 bis-[4-(2,3-epoxipropoxy)phenyl]propane</p>							
	<table border="1"> <tr> <td>Oral</td> <td>LD50</td> <td>>5,000 mg/kg (rat)</td> </tr> <tr> <td>Dermal</td> <td>LD50</td> <td>>5,000 mg/kg (rabbit)</td> </tr> </table>		Oral	LD50	>5,000 mg/kg (rat)	Dermal	LD50	>5,000 mg/kg (rabbit)
Oral	LD50	>5,000 mg/kg (rat)						
Dermal	LD50	>5,000 mg/kg (rabbit)						
	<ul style="list-style-type: none"> · Primary irritant effect: · Skin corrosion/irritation Causes skin irritation. · Serious eye damage/irritation Causes serious eye irritation. · Respiratory or skin sensitisation May cause an allergic skin reaction. · CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. 							

*	SECTION 12: Ecological information					
	<ul style="list-style-type: none"> · 12.1 Toxicity 					
	<ul style="list-style-type: none"> · Aquatic toxicity: 					
	<p>1675-54-3 bis-[4-(2,3-epoxipropoxy)phenyl]propane</p>					
	<table border="1"> <tr> <td>LC50 (96h)</td> <td>2 mg / l (fish)</td> </tr> <tr> <td>EC50 (48h)</td> <td>1.8 mg/l (daphnia)</td> </tr> </table>		LC50 (96h)	2 mg / l (fish)	EC50 (48h)	1.8 mg/l (daphnia)
LC50 (96h)	2 mg / l (fish)					
EC50 (48h)	1.8 mg/l (daphnia)					
	<ul style="list-style-type: none"> · 12.2 Persistence and degradability No further relevant information available. · Other information: The product is not easily biodegradable. 					
	<ul style="list-style-type: none"> · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. 					
	<ul style="list-style-type: none"> · Additional ecological information: 					
	<ul style="list-style-type: none"> · General notes: At present there are no ecotoxicological assessments. 					
	<ul style="list-style-type: none"> · 12.5 Results of PBT and vPvB assessment 					
	<ul style="list-style-type: none"> · PBT: Not applicable. 					
	<ul style="list-style-type: none"> · vPvB: Not applicable. 					
	<ul style="list-style-type: none"> · 12.6 Other adverse effects No further relevant information available. 					

GB

(Contd. on page 6)

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 5)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Dispose of the product by burning in a suitable incinerator or bury in an approved landfield following all applicable local and/or national regulations.

- **European waste catalogue**

20 01 27	paint, inks, adhesives and resins containing dangerous substances
----------	---

- **Uncleaned packaging:**

- **Recommendation:**

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.

Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN3082

- **14.2 UN proper shipping name**

· **ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (epoxy resin)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (epoxy resin)

- **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**

9 Miscellaneous dangerous substances and articles.

· **Label**

9

- **14.4 Packing group**

· **ADR, IMDG, IATA**

III

- **14.5 Environmental hazards:**

· **Marine pollutant:**

Yes

Symbol (fish and tree)

Symbol (fish and tree)

Symbol (fish and tree)

Warning: Miscellaneous dangerous substances and articles.

· **Special marking (ADR):**

· **Special marking (IATA):**

· **14.6 Special precautions for user**

90

· **Danger code (Kemler):**

F-A,S-F

· **EMS Number:**

A

· **Stowage Category**

Not applicable.

· **14.7 Transport in bulk according to Annex II of**

Marpol and the IBC Code

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 13.11.2020

Version number 8

Revision: 13.11.2020

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 6)

· Transport/Additional information:

· ADR	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	-
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· National regulations:

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 8)

GB

**Safety data sheet
according to 1907/2006/EC, Article 31**



Printing date 13.11.2020

Version number 8

Revision: 13.11.2020

Trade name: ADEKIT A 130 RESIN (A)

(Contd. of page 7)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

GB