

PRODUCT DATA SHEET

SikaRoof® Inspection Chamber UK

STANDARD INSPECTION CHAMBER

PRODUCT DESCRIPTION

UV resistant, insensitive to humic acid with inlet slots in walls and cover. A triangle water conduit can be connected to each of the four sides suitable for gravity drainage. Compatible with an automatic irrigation system.

USES

Consisting of base section, side section and lockable cover for use with green roofs to allow inspection of roof drainage outlets.

Please Note: Unsuitable for continuous loads on pedestrian surfaces.

CHARACTERISTICS / ADVANTAGES

- UV resistant
- Extension collars available to suit project requirements

PRODUCT INFORMATION

Chemical Base	ABS recycled plastic	
Packaging	N/A	
Appearance / Colour	Black	
Shelf Life	Product does not expire if correctly stored	
Storage Conditions	All materials to be stored in accordance with good health and safety practice and in accordance with local laws.	
Dimensions	Chamber cross-section	360mm x 3670mm
	Base component floor area	460mm x 460mm
	Chamber base opening	300mm Diameter
	100mm (can be raised in 100mm increments)	
Unit weight	2.4kg	
	TION	

Approximately 150kg (plastic cover)

Product Data Sheet SikaRoof® Inspection

SikaRoof® Inspection Chamber UK May 2021, Version 01.01 020945051350000025

Compression resistance

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION

- Join individual elements by pushing them together until they click into place.
- When using the drainage elements cut out a 350mm x 350mm section above the outlet and position the shaft on the drainage element and filter fleece on top of the outlet.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet SikaRoof® Inspection Chamber UK May 2021, Version 01.01 020945051350000025



SikaRoofInspectionChamberUK-en-GB-(05-2021)-1-1.pdf