

PRODUCT DATA SHEET

Sika® Roll & Stroll Hard Surface Protector

A self adhesive hard surface floor protector

PRODUCT DESCRIPTION

Sika® Roll & Stroll Hard Surface Protector is a premium self adhesive hard surface protector, ideal for protecting against mess, dirt, staining, spillages and soiling that occurs during painting, plastering, building, tiling, general maintenance and repair work. Totally waterproof, Sika® Roll & Stroll Hard Surface Protector protects against expensive to clean paint spillages on hard surfaces. Due to the adhesive face being reverse wound, Sika® Roll & Stroll Hard Surface Protector easily unwinds with minimum effort and no need to bend down.

USES

- Suitable for most hard surfaces, including timber, ceramic tiles, laminate, vinyl, metal and stone.
- Ideal for protecting worktops, window cills, doors and kitchen units.
- Can be used on glass and other smooth surfaces.
- Suitable for both domestic and commercial applications.

PRODUCT INFORMATION

Packaging	600 mm x 25 m roll 600 mm x 75 m roll
Appearance / Colour	Transparent blue film printed with logo in black
Shelf Life	36 months from date of manufacture
Storage Conditions	Store in original, unopened packaging in a cool, dry environment between +5 °C and +25 °C. Protect from direct sunlight, humidity, and temperature extremes, and keep containers upright. Keep out of the reach of children
Thickness	0.05 ± 0.005 mm (50 ± 5 µm)
Tensile Strength	≥18 MPa
Elongation	≥300 %
Thermal Resistance	+60 °C, 160 hours - no residue glue transfer onto hard floor surface after

Slip resistance	Substrate	Pendulum test value	Interpretation	EN 13036-4
	Hard floor - laminate (Dry)	59	Low slip potential	
	Hard floor - laminate (Wet)	24	Medium slip potential	
Bond strength				
Adhesive type: Pressure sensitive acrylic				
Adhesive strength: 180 ± 10 % g/25 mm				

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

This product is for application to hard surfaces, **DO NOT** use on carpets. Use Sika® Roll & Stroll Carpet Protector Ultra/+.

- Adhesion will be reduced on dusty surfaces. Vacuuming or mopping prior to use is recommended.
- Sika® Roll & Stroll Hard Surface Protector must be removed after a maximum of 4 weeks to prevent a sticky residue being left.
- Always check Sika® Roll & Stroll Hard Surface Protector is stuck firmly to surfaces before commencing work.
- On some surfaces Sika® Roll & Stroll Hard Surface Protector may leave a residue, this can be easily removed using Sika® Wonder Wipes or hard surface cleaner. A test area is always recommended prior to full application. Please note when cleaning laminate flooring do not use excess water. Always check compatibility of cleaning agent with sub floor prior to full application.
- In heavily trafficked areas or where air temperature exceeds +22 °C, remove Sika® Roll & Stroll Hard Surface Protector after 1 week maximum. Do not use underfloor heating whilst product is in situ.
- Do not use on surfaces which bleed oils or plasticizers.
- Product may become slippery when wet. Mop up any spills immediately or replace Sika® Roll & Stroll Hard Surface Protector where necessary.
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very

high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

SUBSTRATE PREPARATION

Ensure surfaces are clean, sound, dust free and dry. Remove outer packaging from roll.

APPLICATION METHOD / TOOLS

Ensure surfaces to which Sika® Roll & Stroll Hard Surface Protector is to be applied are clean, sound, dust free and dry. Remove outer packaging from roll. Place roll on the floor facing the direction it is to be applied and unwind approx 300 mm (12 inches) of material. Ensure the roll is stuck by smoothing out by either hand or foot. Simply push roll forward using hands or feet ensuring roll goes in a straight line. Smooth out with hands or feet as it unwinds. A very effective way of laying Sika® Roll & Stroll Hard Surface Protector is to push the roll along with a soft broom/brush using the brush to smooth out and remove air bubbles as it unwinds. For application to worktops, glass etc roll and smooth out by hand until required length is reached. Carefully cut Sika® Roll & Stroll Hard Surface Protector with a sharp knife or scissors, take care not to damage or scratch the covered surface.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Roll & Stroll Hard Surface Protector
October 2026, Version 01.01
02051408000265119

SikaRollStrollHardSurfaceProtector-en-GB-(10-2026)-1-1.pdf