SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Solvent T 660

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

 Telephone no.
 : 01707 394444

 Fax no.
 : 01707 329129

 e-mail address of person
 : EHS@uk.sika.com

responsible for this SDS

le for this SDS

Emergency telephone number : +44 (0)1707 363899 (available during office hours).

1.4 Emergency telephone number

<u>Supplier</u>

Telephone number: +44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F: R11

Xn; R65 Xi; R36/38 R67 N; R51/53

Physical/chemical hazards: Highly flammable.

Human health hazards: Harmful: may cause lung damage if swallowed. Irritating to eyes and skin. Vapours

may cause drowsiness and dizziness.

Environmental hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard symbol or symbols :



Indication of danger : Highly flammable, Harmful, Dangerous for the environment

Date of issue : 06.06.2011. MSDS no. : 122030 1/11

Solvent T 660 06.06.2011 2/11

SECTION 2: Hazards identification

: R11- Highly flammable. Risk phrases

R65- Harmful: may cause lung damage if swallowed.

R36/38- Irritating to eyes and skin.

R67- Vapours may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : Not applicable. Hazardous ingredients : ethyl acetate

naphtha (petroleum), hydrotreated light

Supplemental label

elements

: Not applicable.

2.3 Other hazards

Other hazards which do not: Not available.

result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Chemical family/ : Composition of solvents

Characteristics

		Classification		Type
Product/ingredient name Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
ethyl acetate RRN: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	>= 50 - < 75	F; R11 Xi; R36 R66, R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
naphtha (petroleum), hydrotreated light EC: 265-151-9 CAS: 64742-49-0 Index: 649-328-00-1	>= 25 - < 35	F; R11 Xn; R65 Xi; R38 R67 N; R51/53	Flam. Liq. 2, H225	[1]
		See section 16 for the full text of the R-phrases declared above	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

: 06.06.2011. Date of issue **MSDS no.** : 122030 2/11

Solvent T 660 06.06.2011 3/11

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : If it is suspected that fumes are still present, the rescuer should wear an appropriate

mask or self-contained breathing apparatus. Get medical attention if adverse health

effects persist or are severe. Get medical attention if symptoms appear.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce

vomiting. Maintain an open airway. Seek immediate medical attention.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact: Irritating to eyes.

Inhalation: Vapours may cause drowsiness and dizziness.

Skin contact: Irritating to skin.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage. Irritating to

mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting headache drowsiness/fatigue dizziness/vertigo

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Highly flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may

create fire or explosion hazard.

Date of issue : 06.06.2011. MSDS no. : 122030 3/11

Solvent T 660 06.06.2011 4/11

SECTION 5: Firefighting measures

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide
 carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapour or mist. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a

Date of issue : 06.06.2011. MSDS no. : 122030 4/11

Solvent T 660 06.06.2011 5/11

SECTION 7: Handling and storage

compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions Not available.Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethyl acetate	EH40/2005 WELs (United Kingdom (UK), 8/2007). STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Date of issue : 06.06.2011. MSDS no. : 122030 5/11

Solvent T 660 06.06.2011 6/11

SECTION 8: Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves. (0,4 mm), breakthrough time <30 min. Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapour filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not available.
PH : Not available.
Melting point/freezing point : Not available.

Initial boiling point and boiling

range

: 75°C

Flash point : Closed cup: 0°C

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Burning time : Not applicable.

Burning rate : Not applicable.

Upper/lower flammability or explosive limits : Lower: 0.8%

Upper: 8%

Vapour pressure : 9.7 kPa (72.75 mm Hg)

Vapour density : Not available.

Density : $\sim 0.81 \text{ g/cm}^3 [20^{\circ}\text{C } (68^{\circ}\text{F})]$

Relative density: Not available.Solubility(ies): Not available.Partition coefficient: n-: Not available.

octanol/water

Date of issue : 06.06.2011. MSDS no. : 122030 6/11

Solvent T 660 06.06.2011 7/11

SECTION 9: Physical and chemical properties

Auto-ignition temperature

: 310°C (naphtha (petroleum), hydrotreated light)

Decomposition temperature

: Not available.

Viscosity

: Kinematic (40°C): 0.068 cm²/s

Explosive properties
Oxidising properties

: Not available.: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of reactions

10.3 Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

10.4 Conditions to avoid

: Highly reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous

decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethyl acetate	LC50 Inhalation Vapour LD50 Dermal	Rat Rabbit	1600 mg/l >5000 mg/kg	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary

<u>Irritation/Corrosion</u>

: Not available.

Conclusion/Summary

: Not available.

Sensitisation

Conclusion/Summary

: Not available.

<u>Mutagenicity</u>

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Date of issue : 06.06.2011. MSDS no. : 122030 7/11

Solvent T 660 06.06.2011 8/11

SECTION 11: Toxicological information

Eve contact: Irritating to eyes.

Inhalation: Vapours may cause drowsiness and dizziness.

Skin contact: Irritating to skin.

Ingestion: Aspiration hazard if swallowed. Can enter lungs and cause damage. Irritating to

mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

irritation watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Date of issue : 06.06.2011. MSDS no. : 122030 8/11

Solvent T 660 06.06.2011 9/11

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
ethyl acetate	0.73	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Hazardous waste : package

: packaging containing residues of or contaminated by dangerous substances

European waste catalogue (EWC)

Waste code	Waste designation
07 07 04*	other organic solvents, washing liquids and mother liquors

Packaging

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

SECTION 14: Transport information

	ADR/RID - ADN/ADNR	IMDG	IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	Flammable liquid, n.o.s Solvent naphtha, Ethylacetate	Flammable liquid, n.o.s Solvent naphtha, Ethylacetate	Flammable liquid, n.o.s Solvent naphtha, Ethylacetate
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	No.	No.	No.

Date of issue : 06.06.2011. MSDS no. : 122030 9/11

Solvent T 660 06.06.2011 10/11

SECTION 14: Transport information

14.6 Special precautions for user	Not available.	Not available.	Not available.
Additional information	Special provisions 640D Tunnel code	Emergency schedules (EmS) F-E, S-E	-
	(D/E)		
Classification code	F1		

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions

: Not applicable.

on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

VOC content (EU) : VOC (w/w): 100%

Other EU regulations

REACH Information: : All substances contained in Sika Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by Sika, and/or - excluded from the regulation, and/or

- exempted from the registration.

Europe inventory : All components are listed or exempted.

References : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR)

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Workplace Exposure Limits, HSE (as updated).

HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

15.2 Chemical Safety

Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

: 06.06.2011. Date of issue **MSDS no.** : 122030 10/11

Solvent T 660 06.06.2011 11/11

SECTION 15: Regulatory information

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Full text of abbreviated H

statements

: H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Full text of classifications

[CLP/GHS]

: Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2

STOT SÉ 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE

EXPOSURE) [Narcotic effects] - Category 3

Full text of abbreviated R

phrases

: R11- Highly flammable.

R65- Harmful: may cause lung damage if swallowed.

R36- Irritating to eyes. R38- Irritating to skin.

R36/38- Irritating to eyes and skin.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

[DSD/DPD]

: F - Highly flammable

Xn - Harmful Xi - Irritant

N - Dangerous for the environment

History

Date of printing : 06.06.2011.

Date of issue : 06.06.2011.

Date of previous issue : 26.02.2010.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 06.06.2011. MSDS no. : 122030 11/11