According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaMelt®-677

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H351 Suspected of causing cancer.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P261 Avoid breathing mist or vapours.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

P284 In case of inadequate ventilation wear respir-

atory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

vice/ attention.

Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate n-butyl methacrylate methyl methacrylate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373	>= 2,5 - < 5
		specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity estimate Acute inhalation toxicity (due) 15	
		icity (dust/mist): 1,5 mg/l	
n-butyl methacrylate	97-88-1 202-615-1 01-2119486394-28- XXXX	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1; H317	< 1
methyl methacrylate	80-62-6 201-297-1 01-2119452498-28- XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1; H317	< 1

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

products

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3	GB EH40
			(NCO)	
	Further information: Capable of causing occupational asthma.		al asthma.	
		STEL	0,07 mg/m3	GB EH40
			(NCO)	
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further information: Indicative			
		STEL	100 ppm	2009/161/EU
		STEL	100 ppm	GB EH40
			416 mg/m3	
		TWA	50 ppm	GB EH40
			208 mg/m3	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati-	At the end of the period of exposure	GB EH40 BAT

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Pate of last issue: 02.08.2021 Revision Date: 05.04.2022	Version 8.0	Print Date 05.04.2022
	nine (Urine)	

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

: When handling hot material, wear heat-resistant protective gloves that are able to withstand the temperature of molten

product.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Even at normal processing temperatures it may occur that hot

melts form vapours, which often have an unpleasant odour. If the recommended processing temperatures are exceeded over a fairly long period, additionaly the formation of hazardous organic decomposition products is possible. It is recommended to remove such vapours e.g. by using an efficient

exhauster.

In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

ods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid Colour opaque Odour odourless

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

> 200 °C Flash point

Method: closed cup

Auto-ignition temperature No data available

No data available Decomposition temperature

Not applicable pН

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic Not applicable

Viscosity, kinematic Not applicable

Solubility(ies)

Water solubility insoluble

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,2 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

methyl methacrylate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29,8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Danio rerio (zebra fish)): 9,4 mg/l

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 69 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC: 37 mg/l Exposure time: 21 d

Method: OECD Test Guideline 202

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Revision Date: 05.04.2022

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA (Cargo) Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

4,4'-methylenediphenyl diisocyanate (Number on list 74, 56)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

Not applicable

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

Not applicable

Country GB 000000610784

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Date of last issue: 02.08.2021 Version 8.0 Print Date 05.04.2022

Revision Date: 05.04.2022

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptor
	ties if inhaled.

ms or breathing difficul-

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated

exposure if inhaled.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

CAS

DNEL

Revision Date: 05.04.2022

Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing

a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2009/161/EU / TWA : Limit Value - eight hours 2009/161/EU / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road
: Chemical Abstracts Service
: Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Resp. Sens. 1 H334 Calculation method

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaMelt®-677

Skin Sens. 1 H317 Calculation method Carc. 2 H351 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN