

Sika[®] Epoxy Repair Kit

DECLARATION OF PERFORMANCE

No. 38611363

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	38611363
2	INTENDED USE/S	EN1504-3:2005 Principle 3, Method 3.1. Concrete repair product for non structural repair. PC Mortar (based on epoxy resin)
3	MANUFACTURER:	Sika Limited, Watchmead, Welwyn Garden City, AL7 1BQ, UK
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	2+
6a	DESIGNATED STANDARD:	BS EN 1504-3:2005
	Approved body/ies:	0086

Declaration of Performance

Sika[®] Epoxy Repair Kit
38611363
2026/08 , ver. 01
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Compressive Strength	Class R2	2+	BS EN 1504-3: 2005
Chloride Ion Content	≤0.05%	2+	
Adhesive Bond	≥2.0MPa	2+	
Elastic Modulus	<15GPa	2+	
Thermal Compatibility: Part 4 dry cycling	≥2.0MPa	2+	
Skid Resistance	NPD	2+	
Coefficient of thermal expansion	NPD	2+	
Capillary absorption	<0.5 kg/m ² h ^{0.5}	2+	
Reaction to fire	NPD		
Dangerous substances	Complies with 5.4		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Product Manager
At Leeds on 01 September 2026

Name : Sarah Buchanan
Function: Product Manager
At Leeds on 01 September 2026



End of information as required by UKNI

Declaration of Performance

Sika® Epoxy Repair Kit
38611363
2026/08 , ver. 01
1213



Sika Limited, Welwyn Garden City, UK

DoP No. 38611363

BS EN 1504-3:2005

Approved Body(ies): 0086

Concrete repair product for non structural repair, PC Mortar (based on Epoxy Resin)

Compressive Strength	Class R2
Chloride Ion Content	≤0.05%
Adhesive Bond	≥2.0MPa
Elastic Modulus	<15GPa
Thermal Compatibility: Part 4 dry cycling	≥2.0MPa
Skid Resistance	NPD
Coefficient of thermal expansion	NPD
Capillary absorption	<0.5 kg/m ² h ^{0.5}
Reaction to fire	NPD
Dangerous substances	Complies with 5.4

Declarations of Performance [sika.co.uk](https://www.sika.co.uk)

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sika® Epoxy Repair Kit
38611363
2026/08, ver. 01
1213



Declaration of Performance

Sika® Epoxy Repair Kit

38611363

2026/08 , ver. 01

1213

