

## PRODUCT DATA SHEET

# SikaSeal®-627 Fire Collar

### FIRE RESISTANT PIPE COLLAR

#### PRODUCT DESCRIPTION

SikaSeal®-627 Fire Collar is a fire resistant prefabricated pipe collar consisting of a metal casing and an intumescent insert for interior and exterior penetration sealing applications. SikaSeal®-627 Fire Collar is designed to provide a high volume expansion and pressure seal during a fire to combustible pipes that pass through floor and wall service openings.

#### USES

- Restores the fire resistance performance of a floor or wall which incorporates service openings containing metallic, plastic or composite pipes / conduits.
- Outer face wall or floor application in combination with Sikacryl®-621 Fire
- Can be combined with SikaSeal®-626 Fire Board and Sikacrete®-630 Fire

#### CHARACTERISTICS / ADVANTAGES

- Pipe diameter range 32–250 mm
- Highly intumescent - Volume expansion 20 times original size
- Flexible design enables installation in confined spaces
- Easy to apply - 1 part, 3 fixings for all sizes
- Up to 4 hours fire resistance

#### APPROVALS / STANDARDS

- CE Marking and Declaration of Performance to European Technical Assessment ETA 18/1047, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals
- Fire Collar for Fire Protection EN 1366-3, SikaSeal®-627 Fire Collar, warringtonfire, Approval No. CF 5714
- Fire Collar for Fire Stopping EN 1366-3, EN 13501-1, EN 13501-2, ETAG 026-2, SikaSeal®-627 Fire Collar, UL, Certificate No. UL-EU-01094-CPR
- Fire Resistance Performance Classification EN 13501-2, SikaSeal®-627 Fire Collar, warringtonfire, Classification report No. 401159/E

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Graphite based, intumescent strip
<b>Packaging</b>	Box with 2 collars. Refer to current price list for packaging variations
<b>Appearance / Colour</b>	White casing with anthracite insert
<b>Shelf Life</b>	5 years from the date of production
<b>Storage Conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between -40 °C and +80 °C. Always refer to packaging.

## Dimensions

SikaSeal®-627 Fire Collar is available in the following dimensions.

Inner diameter SikaSeal®-627 Fire Collar	Pipe diameters
32 mm	0–32 mm
40 mm	32–40 mm
55 mm	40–55 mm
63 mm	55–63 mm
75 mm	63–75 mm
82 mm	75–82 mm
90 mm	82–90 mm
110 mm	90–110 mm
125 mm	110–125 mm
140 mm	125–140 mm
160 mm	140–160 mm
200 mm	160–200 mm
250 mm	200–250 mm

## TECHNICAL INFORMATION

<b>Resistance to fire</b>	Refer to 'Approvals / Certificates', Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.
<b>Service Temperature</b>	-20 °C min. / +70 °C max (currently -40 / +120)

## APPLICATION INSTRUCTIONS

### APPLICATION METHOD / TOOLS

Reference must be made to the Sika Method Statement: SikaSeal®-627 Fire Collar

### FURTHER DOCUMENTS

- Sika Method Statement: SikaSeal®-627 Fire Collar
- Sika Passive Fire Protection Handbook
- Fire resistance classification reports

### LIMITATIONS

- Limitations regarding dimensions and configuration described in the relevant fire resistance classification reports must be considered.

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland



**Product Data Sheet**  
SikaSeal®-627 Fire Collar  
June 2020, Version 02.01  
02051510000000013

SikaSeal-627FireCollar-en-GB-(06-2020)-2-1.pdf

