

# Sika<sup>®</sup> Cleaner S

High quality cleaner for heavily soiled surfaces

## Technical Product Data

Chemical base	Organic solvent
Colour	Transparent
Density (CQP <sup>1</sup> 006-3 / ISO 2811-1)	0.9 kg/l approx.
Flash point (CQP 007-1 / ISO 13736)	-20°C (-5°F)
Application temperature	5 - 45°C (40 - 115°F)
Application method	Spray and wipe-off
Storage	Store in sealed container in a cool dry place
Shelf life	24 months

<sup>1)</sup> CQP = Corporate Quality Procedure

### Description

Sika<sup>®</sup> Cleaner S is an organic solvent-based cleaning agent for heavily soiled surfaces that cannot be sufficiently cleaned with standard cleaners.

Sika<sup>®</sup> Cleaner S is manufactured in accordance with ISO 9001 quality assurance system.

### Areas of Application

Sika<sup>®</sup> Cleaner S is designed for cleaning heavily soiled surfaces.

This product is suitable for experienced professional users only. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

### Method of Application

1. Shake can for 10 seconds
  2. Spray a small amount onto the surface from a distance of approx. 5 cm (2 inches)
  3. Spread Sika<sup>®</sup> Cleaner S evenly on the surface and wipe it off
  4. Use Sika<sup>®</sup> Clean-Glass or another suitable glass cleaner to completely clean the surface prior to other pre-treatment steps
  5. Surfaces must be allowed to dry before the next step in surface preparation (e.g. application of Sika<sup>®</sup> Aktivator).
- Tightly re-seal container immediately after each use.

Industry



### Important Note

Before applying Sika® Cleaner S to sensitive surfaces (e.g. plastic, etc.) it is recommended to test Sika® Cleaner S on a small, non-visible area of the base material. Before application of adhesive, the surface must be cleaned and prepared according to Sika's surface preparation recommendations.

### Further Information

Working instructions issued for a defined application may further specify technical data contained in this Product Data Sheet. Copies of the following publications are available on request:

- Material Safety Data Sheets
- Sika Pre-treatment Chart

### Packaging Information

Spray can	400 ml
-----------	--------

### Value Bases

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### Health and Safety Information

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

### Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Further information available at:  
[www.sika.co.uk](http://www.sika.co.uk)  
[www.sika.com](http://www.sika.com)

Sika Limited  
Business Unit Industry  
Watchmead, Welwyn Garden City  
Herts, AL7 1BQ  
United Kingdom  
Tel. +44 (0)1707 394444  
Fax +44 (0)1707 329129

