

PRODUCT DATA SHEET

EVERBUILD® JETCEM® POWDER FILLER

quick setting powder filler

PRODUCT DESCRIPTION

EVERBUILD® JETCEM® POWDER FILLER is a high strength filler in powder form which easily mixes with water to form a creamy lump free paste that is the ideal choice for most decorating repairs. The product dries hard in 1 hour to a smooth sandable finish. The high levels of added polymer ensure this filler will not shrink or crack and is strong enough to accept nails or screws. Suitable for interior and exterior use.

USES

For repairing cracks and holes in:

- Plaster
- Plasterboard
- Brick
- Render
- Wood
- Stone and most other building materials

CHARACTERISTICS / ADVANTAGES

- Sets in 1 hour.
- Easy mixing, just add water.
- Adheres to most common building surfaces.
- Suitable for interior/exterior use.
- Fast, strong and easy to use.
- Overpaintable.

PRODUCT INFORMATION

Packaging	3kg bag
Appearance / Colour	White
Shelf Life	24 months in original unopened bag. This will reduce significantly once opened.
Storage Conditions	Store in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.

APPLICATION INFORMATION

Mixing Ratio	Always use a clean mixing vessel and add approx. 2 ½ parts powder to one part (by volume) clean cold water and mix immediately to a smooth paste.
Pot Life	The mixed filler will remain workable for 30-40 minutes.
Drying time	The filler is normally sandable and overpaintable after approximately one hour. Once dry, sand to a smooth finish. The filler may be painted, papered

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

- Before applying, ensure surfaces are clean, sound and free from dust, crumbly material or any contaminants, which may affect adhesion.
- Cover nail or screw heads with oil based paints and allow to dry.
- Dampen all porous surfaces to improve adhesion.

APPLICATION

- Always use a clean mixing vessel and add approx. 2 ½ parts powder to one part (by volume) clean cold water and mix immediately to a smooth paste. The mixed filler will remain workable for 30-40 minutes.
- Press the filler into the repair with a spreader or filling knife.
- Fill the hole proud to allow for sanding and finish with a wet knife.

CLEANING OF TOOLS

Clean tools etc with warm water before the filler sets.

LIMITATIONS

- For holes deeper than 3cm (1 ½ inch), apply in layers and allow each layer to dry before applying subsequent layers.
- Do not add further water once the filler has started to go off. Remix a fresh batch.
- Allow to fully dry before overcoating.
- Not recommended for overhead repairs. Use EVERBUILD ONE STRIKE FILLER.
- Only use on porous surfaces. Do not apply over plastics, sealants, paints or primers.
- Wood repairs – do not use in areas where impact resistance or flexibility is required, e.g. door surrounds. Use EVERBUILD HIGH PERFORMANCE WOOD FILLER.
- Do not use below 10°C.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited