

PRODUCT DATA SHEET

S-Leafguard round

Prefabricated polypropylene leafguard

PRODUCT DESCRIPTION

S-Leafguard round is a prefabricated Polypropylene (PP) basket with fixing wing nut

USES

This product may only be used by experienced professionals.
The S-Leafguard round is used as a gravel and leaf protection for S-Drains PVC and Sarnafil® T-Drains in flat roofs.

CHARACTERISTICS / ADVANTAGES

- Resistant to UV exposure
- Ease of application
- Recyclable (Delete if recycling facilities or recycling offerings are not available in local country)



PRODUCT INFORMATION

Packaging	Depending on the order quantity and product size, the products are packaged on pallets or in cartons		
Appearance / Colour	Surface	smooth	
	Colour	black	
Shelf Life	5 years from date of production.		
Storage Conditions	The products must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.		
Dimensions	Basket outside diameter	Basket height	Suitable for
	237 mm	82 mm	Sarnafil® T Drain 56 – 160 S-Drain PVC 56 – 160

SYSTEM INFORMATION

System Structure

The following products must be considered for use depending on roof design:

- Sarnafil® T Drain 56 - 160
- S-Drain PVC 56 - 160

APPLICATION INFORMATION

Ambient Air Temperature -20 °C min. / +60 °C max.

Substrate Temperature -30 °C min. / +60 °C max.

APPLICATION INSTRUCTIONS

APPLICATION

Refer to the relevant section in the Installation instructions: Sika® flat roof systems

LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of S-Leafguard round is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

S-Leafguard round
September 2020, Version 01.01
02094505145000004

S-Leafguardround-en-GB-(09-2020)-1-1.pdf