

PRODUCT DATA SHEET

SikaBond® Carpet Adhesive Spray

High tack spray adhesive, ideal for laying carpets

PRODUCT DESCRIPTION

SikaBond® Carpet Adhesive Spray is a high tack contact adhesive, designed for fixing PU backed carpets, carpet tiles, underlay and trims to most common substrates. It can also be used as an upholstery or hobby adhesive.

USES

- Bonding PU backed carpets.
- Bonding carpet tiles to most substrates.
- Bonding metals to most substrates.
- As a multipurpose spray adhesive for hobbies and the home.

CHARACTERISTICS / ADVANTAGES

- Fast rate of tack development.
- Adjustable spray nozzle allows for clean, precise application.
- Easy to apply.
- Time saving application compared to traditional contact adhesives.
- Repositionable.

PRODUCT INFORMATION

Packaging	500 mL aerosol
Colour	Amber
Shelf Life	12 months from date of manufacture
Storage Conditions	Store in original container between +15 °C and +35 °C and away from sources of ignition. Keep out of direct sunlight. Do not allow to freeze.
Thermal Resistance	Up to +60 °C
Yield	Approx. 2.5 m ² per 500 mL canister
Open Time	2 to 5 minutes

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

- Do not use on polystyrene.
- Do not use on cellulose painted surfaces.
- Do not use on bitumen or tar leaching products.
- Medium strength adhesive, do not use on heavily trafficked/industrial areas.

LIMITATIONS

- Do not use to fix vinyl floor tiles.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The surfaces to be bonded should be clean and free from dust, grease and other contaminants. Materials should be stored in a warm environment prior to bonding to avoid chilling of the glue line, which leads to extended setting times.

APPLICATION

Shake the can well before use. Select the fan width by turning the nozzle to the desired position. Spray adhesive from 15 to 20 cm approx (6 to 8 inches) away onto one or both surfaces depending on the type of surface/strength of bond required.

STRONG BONDING:

Apply 1 to 3 coats (depending on strength required) to both surfaces. Allow solvent to evaporate (30 seconds) and press surfaces together from centre outwards.

TEMPORARY REPOSITIONABLE BONDING:

Spray on one surface only and allow to dry for 2 to 3 minutes before bonding.

To prevent spray nozzle from blocking, at the end of each use, turn can upside down and press nozzle until spray is clear of adhesive.

The newly bonded materials should not be subjected to extreme temperature changes for 3 to 4 days after bonding.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaBond® Carpet Adhesive Spray
September 2026, Version 01.01
020512060000264769

SikaBondCarpetAdhesiveSpray-en-GB-(09-2026)-1-1.pdf