

SYSTEM DATA SHEET

SikaCeram® Waterproof Wet Room Kit

For waterproofing showers, wet rooms and wet zones in bathrooms prior to tiling

PRODUCT DESCRIPTION

SikaCeram® Waterproof Wet Room Kit is designed to provide a permanently flexible, watertight membrane prior to tiling in areas such as showers, wet rooms, wet zones in bathrooms and other tiled areas subject to water exposure, such as balconies and partially covered external areas. It is a simple, easy-to-apply 3-part system forming a permanently flexible watertight tank.

USES

- For showers, wet rooms and wet zones in bathrooms.
- Use on all board joints, corners & pipe entries.
- Balconies and partially covered external areas.
- Waterproofing prior to tiling.
- For use on plasterboard, MDF, cementitious boards, brickwork, concrete, specialist wet room boards, plywood etc.

CHARACTERISTICS / ADVANTAGES

- Leaflet with easy reference instructions on all components.
 - All components contained in 1 kit.
 - Standard kit - everything you need to waterproof 4.5 m².
 - Large kit - everything you need to waterproof 7.5 m².
- Both kits come complete with:
- SikaCeram® Tanking Primer (1 L).
 - SikaCeram® Waterproof Tanking Membrane (3 L standard kit, 5 L large kit).
 - SikaCeram® Tanking Tape (10 m).
 - SikaCeram® Tanking Drain Mat.
 - SikaCeram® Wet Room Kit use leaflet.

Shelf life: 24 months.

Storage Conditions: Store in cool, dry conditions between +5 and +25 °C. Storage outside these parameters will dramatically reduce shelf life. Protect from frost.

SUSTAINABILITY INFORMATION

Packaging	Standard - covers 4.5 m² Large - covers 7.5 m²
------------------	---

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not use on timber or boards treated with spirit or stearate based coatings.
- Do not use in areas subject to high temperatures.
- Do not apply below +10 °C.
- Do not apply externally when rain is imminent.

It is the user's responsibility to determine suitability

for use. If in doubt contact Technical Services for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

All surfaces must be clean, dry and free from dust and loose contaminants.

APPLICATION METHOD / TOOLS

Step 1 – SikaCeram® Tanking Primer

- The primer is ready to use. Apply by brush to all porous and semi porous surfaces in the areas that are to be waterproofed. It is quick drying so can be over coated after 1 hour.

Step 2 – SikaCeram® Tanking Tape & SikaCeram® Drain Mat

- A self-adhesive joint & corner sealing butyl backed fleece tape.
- Apply to all corner joints, board joints and pipe penetrations to provide a watertight seal that accommodates cross directional movement.
- On internal corners ensure the tape overlaps on both sides to avoid a weak spot in the centre of the internal corner.
- The kit contains a 10 meter roll which is usually sufficient to waterproof the corners in a 4.5 m² or 7.5 m² application.
- Next apply the self adhesive drain mat around the drain outlet, which is the area most susceptible to water leaks.

Step 3 – SikaCeram® Waterproof Tanking Membrane

- The membrane is a ready to use, non-hazardous liquid waterproofing compound.
- The tape can be over coated with SikaCeram® Waterproof Tanking Membrane immediately after application.
- Apply 2 perpendicular coats by brush to provide a permanently flexible watertight membrane.
- It is quick drying so tiling can commence after 12 hours.

It is recommended a suitable waterproof tile adhesive such as SikaCeram® Flexible Tile Adhesive Ultra and waterproof grout such as SikaCeram® Flexible Grout is used. In addition, all tiled corner joints should be sealed with a waterproof and mould resistant silicone sealant such as the Sika® Forever range.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



System Data Sheet

SikaCeram® Waterproof Wet Room Kit
October 2026, Version 01.01
021790900000266235

SikaCeramWaterproofWetRoomKit-en-GB-(10-2026)-1-1.pdf

