

PRODUCT DATA SHEET

Cromar® Abutment Soaker

Continuous glass reinforced polyester (GRP) dry soaker.

PRODUCT DESCRIPTION

Designed to provide a weatherproof, concealed drainage channel where a pitched roof abuts vertical walls, such as chimneys, parapet walls, or party walls. It acts as a secret gutter, safely collecting and directing rainwater down the roof slope while remaining hidden beneath tiles or slates, offering a durable, lead-free alternative to traditional lead soakers.

USES

- Pitched roofs abutting vertical walls.
- Suitable for slate roofs, and clay or concrete tiles.
- New build and refurbishment projects.
- Domestic and commercial roofing.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Dark Grey
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity.
Storage Conditions	Store in cool, dry place, away from direct sunlight.
Dimensions	140 mm x 3 m

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the

CHARACTERISTICS / ADVANTAGES

- Provides effective protection against water ingress at roof to wall abutments.
- Manufactured from shatter-resistant GRP for long term durability.
- UV-stabilised to prevent degradation and brittleness over time.
- Lightweight and easy to handle, reducing installation time and manual handling risks.

article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Roof underlay is turned up the abutting wall (approx. 100 mm).
- Battens are stopped short of the wall to allow water discharge.
- Soaker is fixed to battens at regular centres.
- Tiles or slates are bedded onto the sanded strip.
- Finished with a flashing over the upstand.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Cromar® Abutment Soaker
March 2026, Version 01.01
020945201000247179

CromarAbutmentSoaker-en-GB-(03-2026)-1-1.pdf