

PRODUCT DATA SHEET

SikaSeal® Removal Tool

Removes all types of flexible sealant from 90° joints

PRODUCT DESCRIPTION

SikaSeal® Removal Tool provides an easy and effective method of removing all types of sealants from any 90° angled joint. The patented design works by gouging the sealant from the bottom of the joint while simultaneously stripping it from both surfaces leaving the area ready for final cleaning and resealing.

USES

Removal of all types of flexible sealant.

PRODUCT INFORMATION

Packaging	One tool
Colour	Blue
Shelf Life	No shelf life determined due to the longevity of plastic items
Storage Conditions	No specific storage requirements

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very

CHARACTERISTICS / ADVANTAGES

- Works on all types of sealants.
- Durable plastic construction.
- Designed for ease of use.

high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Always ensure to push SikaSeal® Removal Tool away from yourself when using, take care of sharp edges.

OPERATING INSTRUCTIONS

Start at one end and push the SikaSeal® Removal Tool into body of sealant until the gouging piece is at the bottom of the joint and both scrapers are flat with the surfaces. Working away from yourself simply push the tool along the joint to remove sealant.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

SikaSeal® Removal Tool
October 2026, Version 01.01
020516040000265867

SikaSealRemovalTool-en-GB-(10-2026)-1-1.pdf