

SikaCeram-277 Flexible Standard Set - White

DECLARATION OF PERFORMANCE No. 89767133

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	SKCM277WE20
2	INTENDED USE/S	Improved Normal setting Deformable cementitious adhesive with reduced slip & extended open time for internal & external tiling
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	3
6a	HARMONISED STANDARD:	EN12004:2007 + A1:2012
	Notified body/ies:	1289

Declaration of Performance

SKCM277WE20

89767133

2021/03 , ver. 01

1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Initial tensile adhesion strength	>1.0 N/mm ²		EN12004:2007 + A1:2012
Tensile strength after 30 minutes open time	> 0.5 N/mm ²		
Tensile adhesion strength after heat aging	>1.0 N/mm ²		
Tensile adhesion strength after freeze thaw cycles	>1.0 N/mm ²		
Tensile adhesion strength after water immersion	>1.0 N/mm ²		
Reaction to fire	NPD		
Reduced slip	<0.5 mm		
Deformable	>2.5 mm		
Release of dangerous substances	See sds		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 05 March 2021



Name : Mariam Maqsood
Function: Product Manager
At Leeds on 08 March 2021

..... 

End of information as required by UKCA

Declaration of Performance

SKCM277WE20
89767133
2021/03 , ver. 03
1213



21

Everbuild Building Products LTD, Leeds, UK

DoP No. 89767133

EN12004:2007 + A1:2012

Notified Body 1289

**Improved Normal setting Deformable cementitious adhesive with reduced slip & extended open time
for internal & external tiling**

Initial tensile adhesion strength	>1.0 N/mm ²
Tensile strength after 30 minutes open time	> 0.5 N/mm ²
Tensile adhesion strength after heat aging	>1.0 N/mm ²
Tensile adhesion strength after freeze thaw cycles	>1.0 N/mm ²
Tensile adhesion strength after water immersion	>1.0 N/mm ²
Reaction to fire	NPD
Reduced slip	<0.5 mm
Deformable	>2.5 mm
Release of dangerous substances	See sds

www.everbuild.co.uk/downloads**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SKCM277WE20

89767133

2021/03 , ver. 03

1213

Declaration of Performance
SKCM277WE20
89767133
2021/03 , ver. 03
1213

