

PRODUCT DATA SHEET

Cromar® Shed Felt

A cost effective waterproof covering.

PRODUCT DESCRIPTION

Designed for use on temporary portable buildings with pitched roofs, such as garden sheds, kennels and other non-habitable buildings. The product is manufactured using a rag-fibre carrier, which is saturated and coated on both sides with oxidised bitumen, then finished with fine mineral on the upper surface and sand on the underside.

USES

Waterproofing membrane for:

- Garden sheds.
- Sectional buildings.
- Portable buildings.
- General timber outbuildings.

CHARACTERISTICS / ADVANTAGES

- Proven traditional roofing felt construction using rag-fibre reinforcement.
- Oxidised bitumen coating for durability and weather protection.
- Fine mineral finish for UV protection and improved longevity.

PRODUCT INFORMATION

Packaging	Sleeved.	
Shelf Life	18 months.	
Storage Conditions	Do not drag rolls across rough surfaces, always lift. Rolls should be stored upright on a dry surface. During colder periods it is recommended that rolls are stored in a temperature above +10 °C for 24 hours prior to use. During storage exposure to direct sunlight is to be avoided. Do not use in temperatures below + 5 °C.	
Dimensions	5 m roll	Green
	10 m roll	Green
	10 m roll	Sand
Width	1 m	
Mass per unit area	1.8 kg m ²	
Tensile Strength	470 N/50 mm MD 325 N/50 mm CD	
Elongation	3 % MD 2 % CD	

Tear Strength 60 N MD
65 N CD

Reaction to Fire EN 13501-1
Class F

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Unroll the membrane and allow it to relax for easier handling.
- Lay the felt with the mineral finished surface facing upwards and the sanded side down.
- Install the felt in horizontal strips starting at the eaves and working upward toward the ridge to ensure correct water shedding.

Fixing:

- Secure the felt using galvanised clout nails along the top edge of each strip.
- Overlap subsequent strips by at least 75 mm.
- Ensure the final ridge strip overlaps both sides to provide full waterproofing.

Finishing:

- Trim felt neatly at edges, ensuring it is tucked and nailed under barge boards or fascia trims for maximum weather protection.
- Avoid installing in wet conditions, as damp decks can trap moisture under the felt.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Shed Felt
March 2026, Version 01.01
020920011970247213

CromarShedFelt-en-GB-(03-2026)-1-1.pdf