

PRODUCT DATA SHEET

SikaShield® Scupper Round UK

Parapet scupper for use with SikaShield® systems

PRODUCT DESCRIPTION

SikaShield® Scupper Round UK are stainless steel scupper outlets incorporating an SBS bitumen flange.

USES

- New build or refurbishment projects
- In conjunction with SikaShield® reinforced bitumen membranes

CHARACTERISTICS / ADVANTAGES

- Stainless steel
- Factory bonded flange
- Flush finish

PRODUCT INFORMATION

Chemical Base	Stainless steel outlet with SBS flange	
Packaging	Cardboard box	
Shelf Life	5 years from date of production	
Storage Conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
Dimensions	500mm x 500mm SBS flange	
Diameter	Diameter (mm)	Spigot Length (mm)
	50	600
	75	600
	110	600
Flow rate	Unit Diameter	Flow Rate (l/s)
	50	0.32
	75	0.63
	110	1.06
*flow rates include use of leaf guard		

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

Please refer to the SikaShield® Installation Guide.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaShield® Scupper Round UK
November 2025, Version 01.01
020945051450245984

SikaShieldScupperRoundUK-en-GB-(11-2025)-1-1.pdf