

## PRODUCT DATA SHEET

# Parex<sup>®</sup> REVLANE + REGULATEUR

### PRIMER FOR SIKA<sup>®</sup> ACRYLIC AND SILOXANE RENDER SYSTEMS

#### DESCRIPTION

REVLANE REGULATEUR is an acrylic-based, ready-to-use coloured primer designed to adjust the base absorption to substrates and increase the depth of colour prior to the application of Parex<sup>®</sup> REVLANE top coat finishes. REVLANE REGULATEUR can be hand or spray applied, is water-vapour permeable and does not create a vapour retarder.

#### USES

Primer for Revlane Acrylic and Siloxane Finishes

#### FEATURES

- Hand or Spray applied
- Water Vapour Permeable
- Ready to use

#### CERTIFICATES AND TEST REPORTS

UKTA-0836-22/6255  
UKTA-0836-22/6256

#### PRODUCT INFORMATION

<b>Composition</b>	<ul style="list-style-type: none"> <li>▪ Binder base: 100 % acrylic.</li> <li>▪ Water based.</li> <li>▪ Colour: white or tinted to desired colour.</li> </ul>
<b>Packaging</b>	20 kg Container
<b>Shelf life</b>	12 Month Shelf Life
<b>Storage conditions</b>	Shelf life applicable when stored in unopened original packing in dry, frost-free conditions. Store away from high temperatures and sources of heat.
<b>Colour</b>	<p>Available in a range of standard shades which will depend upon the finishing colour of the REVLANE top coat finish.</p> <p>Colour references for REVLANE REGULATEUR PRIMER to suit top coat colours</p> <p>PB20 - Blue shades PG00 - White and Cream shades PG30 - Grey shades PG50 - Dark Grey shades PJ40 - Yellow shades PR60 - Red shades PT90 - Orange shades PV30 - Green shades</p>
<b>Density</b>	1.50 ± 0.05 g/cm <sup>3</sup>

# APPLICATION INFORMATION

## Consumption

### COVERAGE

These values are provided as guidance only and may vary subject to substrate conditions.

One coat application: 80 to 100m<sup>2</sup> per container, approximately, depending on the method of application and surface to which it is applied.

## Substrates

### SUITABLE FOR

- In situ and pre-formed concrete.
- Base coats in accordance with BS EN 13914-1.
- Parex® grey one-coat renders e.g. Parmurex\*, Monogris E\*
- Sikatherm and Parextherm range of External Wall Insulation Systems (EWI).
- Parexdirect render systems.
- Internal walls, plaster (gypsum) substrates

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye / face protection. This product contains materials which may cause an allergic reaction, is irritating to eyes and harmful if swallowed. In case of contact, seek medical advice. Keep out of the reach of children. Read and follow the guidelines in the Health and Safety data sheet for this product

## APPLICATION INSTRUCTIONS

### EQUIPMENT

#### EQUIPMENT REQUIRED

- Woollen roller, brush or suitable spray equipment.
- Clean all tools with water after the application.

### APPLICATION

#### INSTRUCTIONS

##### SUBSTRATE PREPARATION

- The substrate must be clean and free from dirt and dust.

##### APPLICATION

- Apply REVLANE REGULATEUR using a woollen roller, brush or spray equipment.
- Allow to dry for 2 to 12 hours according to the temperature and the substrate, before applying the top coat finish.
- REVLANE REGULATEUR must be completely dry before any Parex finish is applied.

#### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

ParexREVLANE+REGULATEUR-en-GBPAREX-(07-2023)-1-1.pdf