

PRODUCT DATA SHEET

EVERBUILD® BLACK JACK® FLASHING TAPE FLASH

Self adhesive flashing tape with a natural lead-look finish

PRODUCT DESCRIPTION

EVERBUILD® BLACK JACK® FLASHING TAPE FLASH is a strong self-adhesive flashing tape comprising of an aluminium foil and a bitumen rubber adhesive. The adhesive forms a strong waterproof seal simply by pressing the tape into place by hand.

USES

- General repair to existing flashing.
- Flashing bituminous felt and similar roofs.
- Flashing parapet walls.
- Replacement of lost lead flashing.
- Repairs to cracks in concrete.
- Repairs to lead gutters.
- Sealing capping bolts in roof sheets.
- Sealing roof ridges.
- Protective coating to insulation materials.
- Sealing projections through roofs and similar sections.
- Flashing between timber and brickwork or blockwork or blockwork cavities.
- Flashing of skylights

CHARACTERISTICS / ADVANTAGES

- Replaces need for lead flashing.
- Self-adhesive - requires no separate glue.

Tape Strength	3.5N/mm
Flexibility at -15°C	No cracking
Application Temperature Range	5°C to 40°C
Weight	1.4 kg/m ²
Bond Strength To Primed Concrete	3.5N/mm

PRODUCT INFORMATION

Packaging	3m DIY Rolls in 100mm, 150mm and 225mm. 10m Trade Rolls in 75mm, 100mm, 150mm, 225mm, 300mm, 450mm.
Appearance / Colour	Lead-look
Shelf Life	24 months from date of manufacture in tightly sealed, undamaged containers.
Storage Conditions	Store in original container in cool (5°C - 25°C) dry conditions.
Thickness	Foil Thickness - 50 µm Adhesive Thickness - 1.3mm

TECHNICAL INFORMATION

Elongation at Break	15%
Service Temperature	-10°C to 80°C

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be dry, sound and free from oil, grease and dust. Remove all loose material by scraper or wire brush. Porous surfaces, such as concrete or brick, should be primed using Black Jack® Bitumen and Flashing Primer and allowed to dry.

APPLICATION METHOD / TOOLS

Cut to the required length. Peel back approximately 5cm of release back cover and place the tape into position. Continue removing the release back cover whilst firmly placing the tape to avoid unnecessary creasing. Ensure intimate contact and that no air is trapped. Using a small roller ensure that all edges and overlaps are sealed properly. Overlaps should be at least 25mm.

LIMITATIONS

- Prime porous surfaces with Black Jack® Bitumen Flashing and Primer.
- Do not apply to damp surfaces.
- In cold weather or storage conditions, adhesion may be reduced. Bring up to temperature or heat bitumen adhesive layer with a hot air blower to improve adhesion.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
EVERBUILD® BLACK
JACK® FLASHING TAPE
FLASH
May 2018, Version
01.01
2/2 0500000000042



EVERBUILDBLACKJACKFLASHINGTAPEFLASH-en-GBEVER-(05-2018)-1-1.pdf

BUILDING TRUST

