

## PRODUCT DATA SHEET

# SikaProof® ExTape-100

Self-adhesive tape for external jointing of the SikaProof® A+ waterproofing system

## PRODUCT DESCRIPTION

SikaProof® ExTape-100 is a self-adhesive tape based on a butyl adhesive for external jointing and detailing of the SikaProof® A+ membrane system. The tape is composed of a grey aluminium/PET carrier and a divided release liner.

## USES

The product is used for:

- Sealing external joints and details within the SikaProof® A+ membrane system.

Please note:

- Do not use the Product in areas where it is permanently exposed to weathering or UV-light.

## CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing ability
- Divided release liner for quick and easy installation

## PRODUCT INFORMATION

<b>Packaging</b>	6 rolls packed in one box. Individual roll size: Length 20 m / Width 100 mm Refer to the current price list for available packaging variations.
<b>Shelf Life</b>	24 months from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between + 5 °C and + 25 °C. Always refer to packaging. Refer to the current price list for available packaging variations.
<b>Appearance / Colour</b>	Grey carrier coated with black butyl adhesive covered by divided white release liner.
<b>Length</b>	20 m
<b>Width</b>	100 mm
<b>Thickness</b>	1.0 mm

## SYSTEM INFORMATION

<b>System Structure</b>	System Components SikaProof® A+ sheet membranes
-------------------------	----------------------------------------------------

# APPLICATION INFORMATION

Ambient Air Temperature	Maximum	+35 °C
	Minimum	+5 °C
Substrate Temperature	Minimum	+5 °C

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

Refer to the following Sika® Method Statement:  
Sika® Method Statement: SikaProof® A+

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### IMPORTANT

#### Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

### IMPORTANT

#### Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

## SUBSTRATE QUALITY

The contact surface is the light yellow SikaProof® membrane side. It must be dry, clean and free of any materials that could impair adhesion.

### Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

## APPLICATION

### IMPORTANT

#### Exposure to UV or weathering

The Product is not resistant to permanent UV exposure or weathering.

- Protect as soon as possible but not later than 90 days after application
1. Remove the release liner
  2. Apply onto the yellow membrane side
  3. Press firmly using a pressure roller

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
SikaProof® ExTape-100  
February 2024, Version 01.01  
020720308000000019

SikaProofExTape-100-en-GB-(02-2024)-1-1.pdf

