

PRODUCT DATA SHEET

Cromar[®] SBS Underlay

SBS modified bitumen underlay.

PRODUCT DESCRIPTION

Cromar[®] SBS Underlay is a HDPE Film SBS modified bitumen torch on membrane. Intended for use as an underlay or intermediate layer in a torch applied built up flat roofing system.

USES

- Application to concrete, timber and metal deck flat roofs.
- Can be used as the covering for garages, sheds and flat roof extensions.
- Intended for use as an underlay or intermediate layer in a torch applied built up flat roofing system.

CHARACTERISTICS / ADVANTAGES

- Torch-on application.
- Can be used on both flat and sloping roofs.
- Ideal for new roofs and the repair of existing felt and asphalt roofs.
- Provides good high temperature performance.
- Resistant to damage and marking during application.

PRODUCT INFORMATION

Packaging	Roll
Colour	Sand and Black.
Shelf Life	18 months
Storage Conditions	Do not drag rolls across rough surfaces, always lift. Rolls should be stored upright on a dry surface. During colder periods it is recommended that rolls are stored at temperatures above + 10 °C for 24 hours prior to use. During storage, exposure to direct sunlight is to be avoided. Do not use in temperatures below + 5 °C.
Length	16 metres
Width	1 metre
Thickness	2 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Cromar®-SBS-Underlay is recommended as a base sheet or intermediate layer in multi-layer waterproofing constructions for flat, pitched or vaulted roofs.
- Cromar®-SBS-Underlay must always be protected by a torch-applied cap sheet membrane (the use of reflective paint is not recommended for this type of membrane). Direct exposure to UV should be avoided.
- Subject to the type of substrate, it shall be installed by means of a propane gas torch or approved adhesives.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® SBS Underlay
May 2026, Version 01.01
020920011990248076

CromarSBSUnderlay-en-GB-(05-2026)-1-1.pdf