according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)





## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaFast®-5211NT (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E H242: Heating may cause a fire.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

TIS 19 Causes serious eye iirila

Precautionary statements : **Prevention:** 

P210 Keep away from heat/sparks/open

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6 Print Date 24.11.201

Sika ®

flames/hot surfaces. No smoking. P234 Keep only in original container.

P280 Wear protective gloves/ protective clothing/

eve protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P411 + P235 Store at temperatures not exceeding 22 °C/

72 °F. Keep cool.

Hazardous components which must be listed on the label:

• 202-327-6 dibenzoyl peroxide

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### **Hazardous components**

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
dibenzoyl peroxide 94-36-0 202-327-6 01-2119511472-50-XXXX	Org. Perox.B; H241 Eye Irrit.2; H319 Skin Sens.1; H317 Aquatic Acute1; H400	>= 10 - < 20

For the full text of the H-Statements mentioned in this Section, see Section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)



Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** : Allergic reactions

**Excessive lachrymation** 

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

May cause an allergic skin reaction.

Causes serious eye irritation.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water, High volume water jet

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

Hazardous combustion prod- : No hazardous combustion products are known

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6



#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic

discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Store in cool place. Keep in a well-ventilated place. Observe label precautions. Store in accord-

ance with local regulations.

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015



Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	GB EH40

### 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)





Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Prevent product from entering drains.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : various

Odour : very faint

Odour Threshold : No data available

Flash point : > 255 °C

Autoignition temperature : Not applicable

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Oxidizing properties : No data available

pH : Note: Not applicable

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,50 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6 Print Date 24.11.2016

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

Decomposes on heating.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids and bases

Reducing agents Heavy metals

## 10.6 Hazardous decomposition products

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

# **Acute toxicity**

Not classified based on available information.

**Components:** 

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 24,3 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6



### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks: No data available

## Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks: Causes serious eye irritation.

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Product:** 

Remarks: May cause an allergic skin reaction.

### Germ cell mutagenicity

Not classified based on available information.

**Product:** 

Germ cell mutagenicity- As- : No data available

sessment

## Carcinogenicity

Not classified based on available information.

**Product:** 

Carcinogenicity - Assess- : No data available

ment

## Reproductive toxicity

Not classified based on available information.

**Product:** 

Reproductive toxicity - As- : No data available

sessment

No data available

# STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

# **Aspiration toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6



# **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Components:**

### dibenzoyl peroxide:

M-Factor : 10

## 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

wav.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional legislation and any regional legislation.

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.


European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Contaminated packaging



: 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

**ADR** 

Not dangerous goods

**IATA** 

Not dangerous goods

**IMDG** 

Not dangerous goods

### 14.6 Special precautions for user

No data available

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: Not applicable

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

**REACH Information:** All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1 50 t

Quantity 2 200 t

P<sub>6</sub>b **SELF-REACTIVE** 

SUBSTANCES AND MIXTURES and ORGANIC

**PEROXIDES** 

VOC-CH (VOCV) : no VOC duties

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)

Revision Date 23.12.2015 Version 2.6



VOC-EU (solvent) : Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

#### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H241 Heating may cause a fire or explosion.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.

#### Full text of other abbreviations

Eye Irrit. Eye irritation
Org. Perox. Organic peroxides
Skin Sens. Skin sensitisation

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

according to Regulation (EC) No. 1907/2006

# SikaFast®-5211NT (B)



Revision Date 23.12.2015 Version 2.6

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!