

SikaControl® WT-250 P

DECLARATION OF PERFORMANCE

No. 88241230

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	88241230
2	INTENDED USE/S	EN 934-2:2009+A1:2012 Water resisting concrete admixture according to BS EN 934-2 (Table 9)
3	MANUFACTURER:	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 934-2:2009+A1:2012
	Notified body:	1029

Declaration of Performance

SikaControl® WT-250 P

88241230

2025.04 , ver. 1

1088

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	<0.1 % w/w	System 2+	EN 934-2:2009+A1:2012
Alkali content	<10.0 % w/w	System 2+	
Capillary absorption	Tested for 7 days after 7 days curing: test mix ≤ 50 % by mass of control mix; tested for 28 days after 90 days curing : test mix ≤ 60 % by mass of control mix	System 2+	
Compressive strength	At 28 days: test mix ≥85% of control mix	System 2+	
Air content	Test mix ≤ 2% by volume above control mix	System 2+	
Corrosion behaviour	Contains only substances according to EN 934-1 Annex A.1	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anthony Smith
 Function: Product Manager
 At Sika Limited on 25 April 2025

Name : Martin Liska
 Function: R&D Manager
 At Sika Limited on 25 April 2025




End of information as required by Regulation (EU) No 305/2011





24

Sika Limited, Hertfordshire, United Kingdom

DoP No. 88241230

EN 934-2:2009+A1:2012

Notified Body 1029

Water resisting concrete admixture according to BS EN 934-2 (Table 9)

Chloride ion content	<0.1 % w/w
Alkali content	<10.0 % w/w
Capillary absorption	Tested for 7 days after 7 days curing: test mix \leq 50 % by mass of control mix; tested for 28 days after 90 days curing : test mix \leq 60 % by mass of control mix
Compressive strength	At 28 days: test mix \geq 85% of control mix
Air content	Test mix \leq 2% by volume above control mix
Corrosion behaviour	Contains only substances according to EN 934-1 Annex A.1

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaControl® WT-250 P

88241230

2025.04 , ver. 1

1088

3/4

BUILDING TRUST



Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire
United Kingdom
<https://gbr.sika.com/>

Declaration of Performance
SikaControl® WT-250 P
88241230
2025.04 , ver. 1
1088

4/4

BUILDING TRUST

